

05/23/00  
1580 U.S. PRO

Please type a plus sign (+) inside this box → ☐ +

Approved for use through 09/30/2000 OMB 0651-0032  
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b> <small>(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))</small>	Attorney Docket No.	NPB002US
	First Inventor or Application Identifier	Kia Silverbrook
	Title	INTERACTIVE PAPER PUBLISHER
	Express Mail Label No.	


<b>APPLICATION ELEMENTS</b> <small>See MPEP chapter 600 concerning utility patent application contents.</small>	<b>ADDRESS TO:</b> Assistant Commissioner for Patents Box Patent Application Washington, DC 20231	
1. <input checked="" type="checkbox"/> * Fee Transmittal Form (e.g., PTO/SB/17) <small>(Submit an original and a duplicate for fee processing)</small>	5. <input type="checkbox"/> Microfiche Computer Program (Appendix)	
2. <input checked="" type="checkbox"/> Specification [Total Pages 90] <small>(preferred arrangement set forth below)</small> <ul style="list-style-type: none"><li>- Descriptive title of the Invention</li><li>- Cross References to Related Applications</li><li>- Statement Regarding Fed sponsored R &amp; D</li><li>- Reference to Microfiche Appendix</li><li>- Background of the Invention</li><li>- Brief Summary of the Invention</li><li>- Brief Description of the Drawings (if filed)</li><li>- Detailed Description</li><li>- Claim(s)</li><li>- Abstract of the Disclosure</li></ul>	6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) <ul style="list-style-type: none"><li>a. <input type="checkbox"/> Computer Readable Copy</li><li>b. <input type="checkbox"/> Paper Copy (identical to computer copy)</li><li>c. <input type="checkbox"/> Statement verifying identity of above copies</li></ul>	
3. <input checked="" type="checkbox"/> Drawing(s) (35 U.S.C. 113) [Total Sheets 46]	<b>ACCOMPANYING APPLICATION PARTS</b> 7. <input checked="" type="checkbox"/> Assignment Papers (cover sheet & document(s)) 8. <input type="checkbox"/> 37 C.F.R. § 3.73(b) Statement <input type="checkbox"/> Power of Attorney <small>(when there is an assignee)</small> 9. <input type="checkbox"/> English Translation Document (if applicable) 10. <input type="checkbox"/> Information Disclosure Statement (IDS)/PTO-1449 <input type="checkbox"/> Copies of IDS Citations 11. <input type="checkbox"/> Preliminary Amendment 12. <input type="checkbox"/> Return Receipt Postcard (MPEP 503) <small>(Should be specifically itemized)</small> 13. <input checked="" type="checkbox"/> * Small Entity Statement(s) <input type="checkbox"/> Statement filed in prior application, Status still proper and desired <small>(PTO/SB/09-12)</small> 14. <input type="checkbox"/> Certified Copy of Priority Document(s) <small>(if foreign priority is claimed)</small> 15. <input type="checkbox"/> Other: .....	
4. Oath or Declaration [Total Pages 3] <ul style="list-style-type: none"><li>a. <input checked="" type="checkbox"/> Newly executed (original or copy)</li><li>b. <input type="checkbox"/> Copy from a prior application (37 C.F.R. § 1.63(d)) <small>(for continuation/divisional with Box 16 completed)</small><ul style="list-style-type: none"><li>i. <input type="checkbox"/> <b>DELETION OF INVENTOR(S)</b> Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).</li></ul></li></ul>		
<b>* NOTE FOR ITEMS 1 &amp; 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).</b>		
16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment: <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application No: _____ Prior application information: Examiner _____ Group / Art Unit: _____ <b>For CONTINUATION or DIVISIONAL APPS only:</b> The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.		

<b>17. CORRESPONDENCE ADDRESS</b>					
<input checked="" type="checkbox"/> Customer Number or Bar Code Label 24011 <small>(Insert Customer No. or Attach bar code label here)</small> or <input type="checkbox"/> Correspondence address below					
Name	Kia Silverbrook Silverbrook Research Pty Ltd				
Address	393 Darling Street				
City	Balmain	State	NSW	Zip Code	2041
Country	AUSTRALIA	Telephone	61-2-9818-6633	Fax	61-2-9818-6711

Name (Print/Type)	Kia Silverbrook	Registration No. (Attorney/Agent)	
Signature		Date	May 16, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

<b>STATEMENT CLAIMING SMALL ENTITY STATUS (37 CFR 1.9(f) &amp; 1.27(c))--SMALL BUSINESS CONCERN</b>	Docket Number (Optional) <b>NPB002US</b>
<p>Applicant, Patentee, or Identifier: <u>Silverbrook Research Pty Ltd</u></p> <p>Application or Patent No.: _____</p> <p>Filed or Issued: <u>May</u>, 2000</p> <p>Title: <u>INTERACTIVE PAPER PUBLISHER</u></p> <p>I hereby state that I am <input checked="" type="checkbox"/> the owner of the small business concern identified below: <input type="checkbox"/> an official of the small business concern empowered to act on behalf of the concern identified below:</p> <p>NAME OF SMALL BUSINESS CONCERN <u>Silverbrook Research Pty. Ltd.</u></p> <p>ADDRESS OF SMALL BUSINESS CONCERN <u>393 Darling Street, Balmain, NSW 2041, Australia</u></p> <p>I hereby state that the above identified small business concern qualifies as a small business concern as defined in 13 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office. Questions related to size standards for a small business concern may be directed to: Small Business Administration, Size Standards Staff, 409 Third Street, SW, Washington, DC 20416.</p> <p>I hereby state that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:</p> <p><input checked="" type="checkbox"/> the specification filed herewith with title as listed above. <input type="checkbox"/> the application identified above. <input type="checkbox"/> the patent identified above.</p> <p>If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).</p> <p>Each person, concern, or organization having any rights in the invention is listed below: <input checked="" type="checkbox"/> no such person, concern, or organization exists. <input type="checkbox"/> each such person, concern, or organization is listed below.</p> <p>Separate statements are required from each named person, concern or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)</p> <p>I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))</p> <p>NAME OF PERSON SIGNING <u>Kia Silverbrook</u></p> <p>TITLE OF PERSON IF OTHER THAN OWNER _____</p> <p>ADDRESS OF PERSON SIGNING <u>393 Darling Street, Balmain, NSW 2041, Australia</u></p> <p>SIGNATURE <u></u> DATE <u>May 16, 2000</u></p>	

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)  
Approved for use through 09/30/2000. OMB 0651-0032  
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. NPT001US  
First Inventor or Application Identifier Paul Lapstun  
Title IDENTITY-CODED INTERFACE  
EXXOSXMMXIXX SURFACE WITH REFERENCE POINTS

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ \* Fee Transmittal Form (e.g., PTO/SB/17)  
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 103]  
(preferred arrangement set forth below)
  - Descriptive title of the Invention
  - Cross References to Related Applications
  - Statement Regarding Fed sponsored R & D
  - Reference to Microfiche Appendix
  - Background of the Invention
  - Brief Summary of the Invention
  - Brief Description of the Drawings (if filed)
  - Detailed Description
  - Claim(s)
  - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 73]
4. Oath or Declaration [Total Pages 3]
  - a. ☒ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))  
(for continuation/divisional with Box 16 completed)
    - i. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

\* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

## ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a. ☐ Computer Readable Copy
  - b. ☐ Paper Copy (identical to computer copy)
  - c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

7. ☒ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement of Power of Attorney (when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 [Copies of IDS Citations]
11. ☐ Preliminary Amendment
12. ☐ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
13. ☒ \* Small Entity Statement filed in prior application, Status still proper and desired (PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☐ Other: .....

## 16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: \_\_\_\_\_ / \_\_\_\_\_


Prior application information: Examiner \_\_\_\_\_ Group / Art Unit: \_\_\_\_\_

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

## 17. CORRESPONDENCE ADDRESS


☒ Customer Number or Bar Code Label 24011 (Insert Customer No. or Attach bar code label here) or ☐ Correspondence address below

Name	Kia Silverbrook				
	Silverbrook Research Pty Ltd				
Address	393 Darling Street				
City	Balmain	State	NSW	Zip Code	2041
Country	AUSTRALIA	Telephone	61-2-9818-6633	Fax	61-2-9818-6711

Name (Print/Type)	Kia Silverbrook	Registration No. (Attorney/Agent)	
Signature		Date	May 16, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

<b>STATEMENT CLAIMING SMALL ENTITY STATUS (37 CFR 1.9(f) &amp; 1.27(c))--SMALL BUSINESS CONCERN</b>	Docket Number (Optional) <b>NPT001US</b>
<p>Applicant, Patentee, or Identifier: <u>Silverbrook Research Pty Ltd</u></p> <p>Application or Patent No.: _____</p> <p>Filed or Issued: <u>May</u>, 2000</p> <p>Title: <u>IDENTITY CODED INTERFACE SURFACE WITH LOCATIONS</u></p> <p>I hereby state that I am <input checked="" type="checkbox"/> the owner of the small business concern identified below: <input type="checkbox"/> an official of the small business concern empowered to act on behalf of the concern identified below:</p> <p>NAME OF SMALL BUSINESS CONCERN <u>Silverbrook Research Pty. Ltd.</u></p> <p>ADDRESS OF SMALL BUSINESS CONCERN <u>393 Darling Street, Balmain, NSW 2041, Australia</u></p> <p>I hereby state that the above identified small business concern qualifies as a small business concern as defined in 13 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office. Questions related to size standards for a small business concern may be directed to: Small Business Administration, Size Standards Staff, 409 Third Street, SW, Washington, DC 20416.</p> <p>I hereby state that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:</p> <p><input checked="" type="checkbox"/> the specification filed herewith with title as listed above. <input type="checkbox"/> the application identified above. <input type="checkbox"/> the patent identified above.</p> <p>If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).</p> <p>Each person, concern, or organization having any rights in the invention is listed below: <input checked="" type="checkbox"/> no such person, concern, or organization exists. <input type="checkbox"/> each such person, concern, or organization is listed below.</p> <p>Separate statements are required from each named person, concern or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)</p> <p>I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))</p> <p>NAME OF PERSON SIGNING <u>Kia Silverbrook</u></p> <p>TITLE OF PERSON IF OTHER THAN OWNER _____</p> <p>ADDRESS OF PERSON SIGNING <u>393 Darling Street, Balmain, NSW 2041, Australia</u></p> <p>SIGNATURE <u></u> DATE <u>May 16, 2000</u></p>	

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

## IDENTITY-CODED SURFACE WITH REFERENCE POINTS

### FIELD OF INVENTION

The present invention relates generally to a method of defining a region in relation to a surface, and to a region so defined.

- 5           The invention has been developed primarily to provide the basis for a surface-based interface which allows a user to input and interact with information via a network, and to obtain interactive printed matter on demand via high-speed networked color printers. Although the invention will largely be described herein with reference to this use, it will be appreciated that the invention is not limited to use in this field.

### 10 CO-PENDING APPLICATIONS

Various methods, systems and apparatus relating to the present invention are disclosed in the following co-pending applications filed by the applicant or assignee of the present invention simultaneously with the present application:

- 15           NPA001US, NPA002US, NPA003US, NPA004US, NPA005US, NPA006US, NPA007US, NPA008US, NPA009US, NPA010US, NPA012US, NPA016US, NPA017US, NPA018US, NPA019US, NPA020US, NPA021US, NPA030US, NPA035US, NPA048US, NPA050US, NPA051US, NPA052US, NPA075US, NPB001US, NPB002US, NPK002US, NPK003US, NPK004US, NPK005US, NPK007US, NPM001US, NPM002US, NPM003US, NPM004US, NPN001US, NPN002US, NPN003US, NPP001US, NPP002US, NPP003US, NPP005US, NPP006US, NPP007US, NPP008US, NPP016US, NPP017US, NPP018US, NPP019US, NPS001US, NPS003US, NPS020US, NPT001US, NPT002US, NPT003US, NPT004US, NPX001US, NPX003US, NPX008US, NPX011US, NPX014US, NPX016US, NPX020US, NPX022US, IJ52US, IJM52US, MJ10US, MJ11US, MJ12US, MJ13US, MJ14US, MJ15US, MJ34US, MJ47US, MJ52US, MJ58US, MJ62US, MJ63US, PAK04US, PAK05US, PAK06US, PAK07US, PAK08US, PEC01US, PEC02US.
- 20
- 25

- The disclosures of these co-pending applications are incorporated herein by cross-reference. Each application is temporarily identified by its docket number. This will be replaced by the corresponding USSN when available.
- 30

## BACKGROUND

Presently, the majority of forms for accepting input from a user are either printed on paper or displayed on a computer screen. With a paper-based form, the user writes information on the form by hand, usually in spaces or boxes provided adjacent  
5 printed questions or instructions. The information is later keyed into a computer system for online storage processing and storage. With a screen-based form, the user enters information into the form via a computer keyboard. Both of these approaches have disadvantages. The screen-based approach is convenient to the form recipient, but requires that the user have access to a computer system. By contrast, the paper-based  
10 approach only requires the user to apply pen to paper, but requires the form recipient to wait for manual delivery of the form and perform data entry of its content.

## OBJECT

It is an object of the present invention to combine advantages of paper-based forms and immediate online information capture.

## 15 SUMMARY OF INVENTION

According to a first aspect of the present invention, there is provided a region defined in relation to a surface, coded data being disposed within the region, wherein the coded data is indicative of:

- a region identity associated with the region; and
- 20 a plurality of points within the region.

According to a second aspect of the present invention, there is provided a surface, the surface including a region according to the first aspect.

According to a third aspect of the present invention, there is provided a method of producing a surface having a region, the method including the steps of:

- 25 (a) defining coded data, the coded data being indicative of:
  - a region identity associated with the region; and
  - a plurality of points within the region;
- (b) disposing the coded data within a region on the surface.

Preferably, the coded data includes at least one tag, each tag being indicative of the region identity and the position of the tag within the region. More preferably, each of the tags includes first identity data defining a relative position of that tag, and second identity data identifying the surface.

- 5           In a particularly preferred form, the tags are printed onto a surface in the form of a piece of paper, and are configured to be read by a sensing device in the form of an optical sensing stylus. The tags are preferably printed using an ink that absorbs near infrared light but is substantially invisible to a human viewer under normal lighting conditions. When a user brings a sensing end of the stylus close to the surface, one or
- 10   more of the tags are imaged, interpreted and decoded to provide an indication of the identity of the region from which the tag was imaged, and a position of the read tag within the region. This information can be used in a number of useful ways, including controlling a computer via interactive elements or providing input to a computer for storage, manipulation or display.
- 15           Further aspects of the invention will become apparent from reading the following detailed description of preferred and other embodiments of the invention.

## BRIEF DESCRIPTION OF DRAWINGS

Preferred and other embodiments of the invention will now be described, by way of non-limiting example only, with reference to the accompanying drawings, in which:

- 5 Figure 1 is a schematic of a the relationship between a sample printed netpage and its online page description;

Figure 2 is a schematic view of a interaction between a netpage pen, a netpage printer, a netpage page server, and a netpage application server;

- 10 Figure 3 illustrates a collection of netpage servers and printers interconnected via a network;

Figure 4 is a schematic view of a high-level structure of a printed netpage and its online page description;

Figure 5 is a plan view showing a structure of a netpage tag;

- 15 Figure 6 is a plan view showing a relationship between a set of the tags shown in Figure 5 and a field of view of a netpage sensing device in the form of a netpage pen;

Figure 7 is a flowchart of a tag image processing and decoding algorithm;

Figure 8 is a perspective view of a netpage pen and its associated tag-sensing field-of-view cone;

Figure 9 is a perspective exploded view of the netpage pen shown in Figure 8;

- 20 Figure 10 is a schematic block diagram of a pen controller for the netpage pen shown in Figures 8 and 9;

Figure 11 is a perspective view of a wall-mounted netpage printer;

Figure 12 is a section through the length of the netpage printer of Figure 11;

- 25 Figure 12a is an enlarged portion of Figure 12 showing a section of the duplexed print engines and glue wheel assembly;

Figure 13 is a detailed view of the ink cartridge, ink, air and glue paths, and print engines of the netpage printer of Figures 11 and 12;

Figure 14 is a schematic block diagram of a printer controller for the netpage printer



shown in Figures 11 and 12;

Figure 15 is a schematic block diagram of duplexed print engine controllers and Memjet™ printheads associated with the printer controller shown in Figure 14;

Figure 16 is a schematic block diagram of the print engine controller shown in Figures 5 14 and 15;

Figure 17 is a perspective view of a single Memjet™ printing element, as used in, for example, the netpage printer of Figures 10 to 12;

Figure 18 is a perspective view of a small part of an array of Memjet™ printing elements;

10 Figure 19 is a series of perspective views illustrating the operating cycle of the Memjet™ printing element shown in Figure 13;

Figure 20 is a perspective view of a short segment of a pagewidth Memjet™ printhead;

Figure 21 is a schematic view of a user class diagram;

Figure 22 is a schematic view of a printer class diagram;

15 Figure 23 is a schematic view of a pen class diagram;

Figure 24 is a schematic view of an application class diagram;

Figure 25 is a schematic view of a document and page description class diagram;

Figure 26 is a schematic view of a document and page ownership class diagram;

Figure 27 is a schematic view of a terminal element specialization class diagram;

20 Figure 28 is a schematic view of a static element specialization class diagram;

Figure 29 is a schematic view of a hyperlink element class diagram;

Figure 30 is a schematic view of a hyperlink element specialization class diagram;

Figure 31 is a schematic view of a hyperlinked group class diagram;

Figure 32 is a schematic view of a form class diagram;

25 Figure 33 is a schematic view of a digital ink class diagram;

Figure 34 is a schematic view of a field element specialization class diagram;

Figure 35 is a schematic view of a checkbox field class diagram;

Figure 36 is a schematic view of a text field class diagram;

Figure 37 is a schematic view of a signature field class diagram;

Figure 38 is a flowchart of an input processing algorithm;

- 5 Figure 38a is a detailed flowchart of one step of the flowchart of Figure 38;

Figure 39 is a schematic view of a page server command element class diagram;

Figure 40 is a schematic view of a resource description class diagram;

Figure 41 is a schematic view of a favorites list class diagram;

Figure 42 is a schematic view of a history list class diagram;

- 10 Figure 43 is a schematic view of a subscription delivery protocol;

Figure 44 is a schematic view of a hyperlink request class diagram;

Figure 45 is a schematic view of a hyperlink activation protocol;

Figure 46 is a schematic view of a form submission protocol;

Figure 47 is a schematic view of a commission payment protocol;

- 15 Figure 48 is a schematic view of a set of radial wedges making up a symbol;

Figure 49 is a schematic view of a ring A and B symbol allocation scheme;

Figure 50 is a schematic view of a first ring C and D symbol allocation scheme;

Figure 51 is a schematic view of a second ring C and D symbol allocation scheme;

Figure 52 is a schematic view of a triangular tag packing;

- 20 Figure 53 is a perspective view of an icosahedron;

Figure 54 is a perspective view of an icosahedral geodesic with frequency 3;

Figure 55 is a schematic view of a minimum tag spacing;

Figure 56 is a schematic view of a minimum tag spacing which avoids overlap;

Figure 57 is a schematic view of a first tag insertion case;

- 25 Figure 58 is a schematic view of a second tag insertion case;

Figure 59 is a schematic view of a third tag insertion case;

Figure 60 is a schematic view of a fourth tag insertion case;

Figure 61 is a schematic view of a pen orientation relative to a surface;

Figure 62 is a schematic view of a pen pitch geometry;

5 Figure 63 is a schematic view of a pen roll geometry;

Figure 64 is a schematic view of a pen coordinate space showing physical and optical axes of a pen;

Figure 65 is a schematic view of a curved nib geometry;

10 Figure 66 is a schematic view of an interaction between sampling frequency and tag frequency;

Figure 67 is a table containing equations numbered 1 to 10;

Figure 68 is a table containing equations numbered 11 to 20;

Figure 69 is a table containing equations numbered 21 to 26;

Figure 70 is a table containing equations numbered 27 to 34;

15 Figure 71 is a table containing equations numbered 35 to 41;

Figure 72 is a table containing equations numbered 42 to 44;

Figure 73 is a table containing equations numbered 45 to 47;

Figure 74 is a table containing equations numbered 48 to 51;

Figure 75 is a table containing equations numbered 52 to 54;

20 Figure 76 is a table containing equations numbered 55 to 57;

Figure 77 is a table containing equations numbered 58 to 59;

Figure 78 is a table containing equations numbered 60 to 63;

Figure 79 is a table containing equations numbered 64 to 74;

Figure 80 is a table containing equations numbered 75 to 86;

25 Figure 81 is a table containing equations numbered 87 to 99;

Figure 82 is a table containing equations numbered 100 to 111;

Figure 83 is a table containing equations numbered 112 to 120;

Figure 84 is a table containing equations numbered 121 to 129;

Figure 85 is a table containing a set of degenerate forms of equations 64 to 71;

Figure 86 is a first part of a table containing conditions and special handling for zero  
5 pitch and zero roll; and

Figure 87 is a the second part of the table of Figure 86.

## DETAILED DESCRIPTION OF PREFERRED AND OTHER EMBODIMENTS

Note: Memjet™ is a trade mark of Silverbrook Research Pty Ltd, Australia.

In the preferred embodiment, the invention is configured to work with the netpage networked computer system, a detailed overview of which follows. It will be appreciated that not every implementation will necessarily embody all or even most of the specific details and extensions discussed below in relation to the basic system. However, the system is described in its most complete form to reduce the need for external reference when attempting to understand the context in which the preferred embodiments and aspects of the present invention operate.

In brief summary, the preferred form of the netpage system employs a computer interface in the form of a mapped surface, that is, a physical surface which contains references to a map of the surface maintained in a computer system. The map references can be queried by an appropriate sensing device. Depending upon the specific implementation, the map references may be encoded visibly or invisibly, and defined in such a way that a local query on the mapped surface yields an unambiguous map reference both within the map and among different maps. The computer system can contain information about features on the mapped surface, and such information can be retrieved based on map references supplied by a sensing device used with the mapped surface. The information thus retrieved can take the form of actions which are initiated by the computer system on behalf of the operator in response to the operator's interaction with the surface features.

In its preferred form, the netpage system relies on the production of, and human interaction with, netpages. These are pages of text, graphics and images printed on ordinary paper, but which work like interactive web pages. Information is encoded on each page using ink which is substantially invisible to the unaided human eye. The ink, however, and thereby the coded data, can be sensed by an optically imaging pen and transmitted to the netpage system.

In the preferred form, active buttons and hyperlinks on each page can be clicked with the pen to request information from the network or to signal preferences to a network server. In one embodiment, text written by hand on a netpage is automatically recognized and converted to computer text in the netpage system, allowing forms to be

filled in. In other embodiments, signatures recorded on a netpage are automatically verified, allowing e-commerce transactions to be securely authorized.

As illustrated in Figure 1, a printed netpage 1 can represent a interactive form which can be filled in by the user both physically, on the printed page, and  
5 “electronically”, via communication between the pen and the netpage system. The example shows a “Request” form containing name and address fields and a submit button. The netpage consists of graphic data 2 printed using visible ink, and coded data 3 printed as a collection of tags 4 using invisible ink. The corresponding page description  
10 5, stored on the netpage network, describes the individual elements of the netpage. In particular it describes the type and spatial extent (zone) of each interactive element (i.e. text field or button in the example), to allow the netpage system to correctly interpret input via the netpage. The submit button 6, for example, has a zone 7 which corresponds to the spatial extent of the corresponding graphic 8.

As illustrated in Figure 2, the netpage pen 101, a preferred form of which is  
15 shown in Figures 8 and 9 and described in more detail below, works in conjunction with a netpage printer 601, an Internet-connected printing appliance for home, office or mobile use. The pen is wireless and communicates securely with the netpage printer via a short-range radio link 9.

The netpage printer 601, a preferred form of which is shown in Figures 11 to  
20 13 and described in more detail below, is able to deliver, periodically or on demand, personalized newspapers, magazines, catalogs, brochures and other publications, all printed at high quality as interactive netpages. Unlike a personal computer, the netpage printer is an appliance which can be, for example, wall-mounted adjacent to an area where the morning news is first consumed, such as in a user’s kitchen, near a breakfast  
25 table, or near the household’s point of departure for the day. It also comes in tabletop, desktop, portable and miniature versions.

Netpages printed at their point of consumption combine the ease-of-use of paper with the timeliness and interactivity of an interactive medium.

As shown in Figure 2, the netpage pen 101 interacts with the coded data on a  
30 printed netpage 1 and communicates, via a short-range radio link 9, the interaction to a netpage printer. The printer 601 sends the interaction to the relevant netpage page server

10 for interpretation. In appropriate circumstances, the page server sends a corresponding message to application computer software running on a netpage application server 13. The application server may in turn send a response which is printed on the originating printer.

5           The netpage system is made considerably more convenient in the preferred embodiment by being used in conjunction with high-speed microelectromechanical system (MEMS) based inkjet (Memjet™) printers. In the preferred form of this technology, relatively high-speed and high-quality printing is made more affordable to consumers. In its preferred form, a netpage publication has the physical characteristics of  
10 a traditional newsmagazine, such as a set of letter-size glossy pages printed in full color on both sides, bound together for easy navigation and comfortable handling.

          The netpage printer exploits the growing availability of broadband Internet access. Cable service is available to 95% of households in the United States, and cable modem service offering broadband Internet access is already available to 20% of these.  
15 The netpage printer can also operate with slower connections, but with longer delivery times and lower image quality. Indeed, the netpage system can be enabled using existing consumer inkjet and laser printers, although the system will operate more slowly and will therefore be less acceptable from a consumer's point of view. In other embodiments, the netpage system is hosted on a private intranet. In still other embodiments, the netpage  
20 system is hosted on a single computer or computer-enabled device, such as a printer.

          Netpage publication servers 14 on the netpage network are configured to deliver print-quality publications to netpage printers. Periodical publications are delivered automatically to subscribing netpage printers via pointcasting and multicasting Internet protocols. Personalized publications are filtered and formatted according to  
25 individual user profiles.

          A netpage printer can be configured to support any number of pens, and a pen can work with any number of netpage printers. In the preferred implementation, each netpage pen has a unique identifier. A household may have a collection of colored netpage pens, one assigned to each member of the family. This allows each user to  
30 maintain a distinct profile with respect to a netpage publication server or application server.

A netpage pen can also be registered with a netpage registration server 11 and linked to one or more payment card accounts. This allows e-commerce payments to be securely authorized using the netpage pen. The netpage registration server compares the signature captured by the netpage pen with a previously registered signature, allowing it to authenticate the user's identity to an e-commerce server. Other biometrics can also be used to verify identity. A version of the netpage pen includes fingerprint scanning, verified in a similar way by the netpage registration server.

Although a netpage printer may deliver periodicals such as the morning newspaper without user intervention, it can be configured never to deliver unsolicited junk mail. In its preferred form, it only delivers periodicals from subscribed or otherwise authorized sources. In this respect, the netpage printer is unlike a fax machine or e-mail account which is visible to any junk mailer who knows the telephone number or email address.

## **1 NETPAGE SYSTEM ARCHITECTURE**

Each object model in the system is described using a Unified Modeling Language (UML) class diagram. A class diagram consists of a set of object classes connected by relationships, and two kinds of relationships are of interest here: associations and generalizations. An association represents some kind of relationship between objects, i.e. between instances of classes. A generalization relates actual classes, and can be understood in the following way: if a class is thought of as the set of all objects of that class, and class A is a generalization of class B, then B is simply a subset of A. The UML does not directly support second-order modelling - i.e. classes of classes.

Each class is drawn as a rectangle labelled with the name of the class. It contains a list of the attributes of the class, separated from the name by a horizontal line, and a list of the operations of the class, separated from the attribute list by a horizontal line. In the class diagrams which follow, however, operations are never modelled.

An association is drawn as a line joining two classes, optionally labelled at either end with the multiplicity of the association. The default multiplicity is one. An asterisk (\*) indicates a multiplicity of "many", i.e. zero or more. Each association is optionally labelled with its name, and is also optionally labelled at either end with the role of the corresponding class. An open diamond indicates an aggregation association



("is-part-of"), and is drawn at the aggregator end of the association line.

A generalization relationship ("is-a") is drawn as a solid line joining two classes, with an arrow (in the form of an open triangle) at the generalization end.

When a class diagram is broken up into multiple diagrams, any class which is  
5 duplicated is shown with a dashed outline in all but the main diagram which defines it. It is shown with attributes only where it is defined.

## 1.1 NETPAGES

Netpages are the foundation on which a netpage network is built. They provide a paper-based user interface to published information and interactive services.

10 A netpage consists of a printed page (or other surface region) invisibly tagged with references to an online description of the page. The online page description is maintained persistently by a netpage page server. The page description describes the visible layout and content of the page, including text, graphics and images. It also describes the input elements on the page, including buttons, hyperlinks, and input fields.  
15 A netpage allows markings made with a netpage pen on its surface to be simultaneously captured and processed by the netpage system.

Multiple netpages can share the same page description. However, to allow input through otherwise identical pages to be distinguished, each netpage is assigned a unique page identifier. This page ID has sufficient precision to distinguish between a  
20 very large number of netpages.

Each reference to the page description is encoded in a printed tag. The tag identifies the unique page on which it appears, and thereby indirectly identifies the page description. The tag also identifies its own position on the page. Characteristics of the tags are described in more detail below.

25 Tags are printed in infrared-absorptive ink on any substrate which is infrared-reflective, such as ordinary paper. Near-infrared wavelengths are invisible to the human eye but are easily sensed by a solid-state image sensor with an appropriate filter.

A tag is sensed by an area image sensor in the netpage pen, and the tag data is transmitted to the netpage system via the nearest netpage printer. The pen is wireless and  
30 communicates with the netpage printer via a short-range radio link. Tags are sufficiently

small and densely arranged that the pen can reliably image at least one tag even on a single click on the page. It is important that the pen recognize the page ID and position on every interaction with the page, since the interaction is stateless. Tags are error-correctably encoded to make them partially tolerant to surface damage.

- 5           The netpage page server maintains a unique page instance for each printed netpage, allowing it to maintain a distinct set of user-supplied values for input fields in the page description for each printed netpage.

          The relationship between the page description, the page instance, and the printed netpage is shown in Figure 4. The page instance is associated with both the  
10       netpage printer which printed it and, if known, the netpage user who requested it.

## **1.2       NETPAGE TAGS**

### **1.2.1    Tag Data Content**

          In a preferred form, each tag identifies the region in which it appears, and the location of that tag within the region. A tag may also contain flags which relate to the  
15       region as a whole or to the tag. One or more flag bits may, for example, signal a tag sensing device to provide feedback indicative of a function associated with the immediate area of the tag, without the sensing device having to refer to a description of the region. A netpage pen may, for example, illuminate an “active area” LED when in the zone of a hyperlink.

20           As will be more clearly explained below, in a preferred embodiment, each tag contains an easily recognized invariant structure which aids initial detection, and which assists in minimizing the effect of any warp induced by the surface or by the sensing process. The tags preferably tile the entire page, and are sufficiently small and densely arranged that the pen can reliably image at least one tag even on a single click on the  
25       page. It is important that the pen recognize the page ID and position on every interaction with the page, since the interaction is stateless.

          In a preferred embodiment, the region to which a tag refers coincides with an entire page, and the region ID encoded in the tag is therefore synonymous with the page ID of the page on which the tag appears. In other embodiments, the region to which a tag  
30       refers can be an arbitrary subregion of a page or other surface. For example, it can

coincide with the zone of an interactive element, in which case the region ID can directly identify the interactive element.

**Table 1. Tag data**

Field	Precision (bits)
Region ID	100
Tag ID	16
Flags	4
Total	120

5            Each tag contains 120 bits of information, typically allocated as shown in Table  
1. Assuming a maximum tag density of 64 per square inch, a 16-bit tag ID supports a  
region size of up to 1024 square inches. Larger regions can be mapped continuously  
without increasing the tag ID precision simply by using abutting regions and maps. The  
100-bit region ID allows  $2^{100}$  ( $\sim 10^{30}$  or a million trillion trillion) different regions to be  
10 uniquely identified.

### **1.2.2 Tag Data Encoding**

The 120 bits of tag data are redundantly encoded using a (15, 5) Reed-Solomon  
code. This yields 360 encoded bits consisting of 6 codewords of 15 4-bit symbols each.  
The (15, 5) code allows up to 5 symbol errors to be corrected per codeword, i.e. it is  
15 tolerant of a symbol error rate of up to 33% per codeword.

Each 4-bit symbol is represented in a spatially coherent way in the tag, and the  
symbols of the six codewords are interleaved spatially within the tag. This ensures that a  
burst error (an error affecting multiple spatially adjacent bits) damages a minimum  
number of symbols overall and a minimum number of symbols in any one codeword,  
20 thus maximising the likelihood that the burst error can be fully corrected.

### **1.2.3 Physical Tag Structure**

The physical representation of the tag, shown in Figure 5, includes fixed target  
structures 15, 16, 17 and variable data areas 18. The fixed target structures allow a  
sensing device such as the netpage pen to detect the tag and infer its three-dimensional  
25 orientation relative to the sensor. The data areas contain representations of the individual  
bits of the encoded tag data.

To achieve proper tag reproduction, the tag is rendered at a resolution of 256×256 dots. When printed at 1600 dots per inch this yields a tag with a diameter of about 4 mm. At this resolution the tag is designed to be surrounded by a “quiet area” of radius 16 dots. Since the quiet area is also contributed by adjacent tags, it only adds 16  
5 dots to the effective diameter of the tag.

The tag includes six target structures: a detection ring 15; an orientation axis target 16; and four perspective targets 17.

The detection ring 15 allows the sensing device to initially detect the tag 4. The ring is easy to detect because it is rotationally invariant and because a simple correction  
10 of its aspect ratio removes most of the effects of perspective distortion. The orientation axis 16 allows the sensing device to determine the approximate planar orientation of the tag due to the yaw of the sensor. The orientation axis is skewed to yield a unique orientation. The four perspective targets 17 allow the sensing device to infer an accurate two-dimensional perspective transform of the tag and hence an accurate three-  
15 dimensional position and orientation of the tag relative to the sensor.

All target structures are redundantly large to improve their immunity to noise.

The overall tag shape is circular. This supports, amongst other things, optimal tag packing on an irregular triangular grid. In combination with the circular detection ring 15, this makes a circular arrangement of data bits within the tag optimal. To  
20 maximise its size, each data bit is represented by a radial wedge 510 in the form of an area bounded by two radial lines 512, a radially inner arc 514 and a radially outer arc 516. Each wedge 510 has a minimum dimension of 8 dots at 1600 dpi and is designed so that its base (i.e. its inner arc 514), is at least equal to this minimum dimension. The radial height of the wedge 510 is always equal to the minimum dimension. Each 4-bit  
25 data symbol is represented by an array 518 of 2×2 wedges 510, as best shown in Figure 48.

The 15 4-bit data symbols of each of the six codewords are allocated to the four concentric symbol rings 18a to 18d, shown in Figure 5, in interleaved fashion as shown in Figures 49 to 51. Symbols of first to sixth codewords 520-525 are allocated alternately  
30 in circular progression around the tag.

The interleaving is designed to maximise the average spatial distance between any two symbols of the same codeword.

In order to support “single-click” interaction with a tagged region via a sensing device, the sensing device must be able to see at least one entire tag in its field of view  
5 no matter where in the region or at what orientation it is positioned. The required diameter of the field of view of the sensing device is therefore a function of the size and spacing of the tags.

Assuming a circular tag shape, the minimum diameter of the sensor field of view is obtained when the tags are tiled on an equilateral triangular grid, as shown in  
10 Figure 6.

#### 1.2.4 Tag Image Processing and Decoding

The tag image processing and decoding performed by a sensing device such as the netpage pen is shown in Figure 7. While a captured image is being acquired from the image sensor, the dynamic range of the image is determined (at 20). The center of the  
15 range is then chosen as the binary threshold for the image 21. The image is then thresholded and segmented into connected pixel regions (i.e. shapes 23) (at 22). Shapes which are too small to represent tag target structures are discarded. The size and centroid of each shape is also computed.

Binary shape moments 25 are then computed (at 24) for each shape, and these  
20 provide the basis for subsequently locating target structures. Central shape moments are by their nature invariant of position, and can be easily made invariant of scale, aspect ratio and rotation.

The ring target structure 15 is the first to be located (at 26). A ring has the advantage of being very well behaved when perspective-distorted. Matching proceeds by  
25 aspect-normalizing and rotation-normalizing each shape’s moments. Once its second-order moments are normalized the ring is easy to recognize even if the perspective distortion was significant. The ring’s original aspect and rotation 27 together provide a useful approximation of the perspective transform.

The axis target structure 16 is the next to be located (at 28). Matching proceeds  
30 by applying the ring’s normalizations to each shape’s moments, and rotation-normalizing

the resulting moments. Once its second-order moments are normalized the axis target is easily recognized. Note that one third order moment is required to disambiguate the two possible orientations of the axis. The shape is deliberately skewed to one side to make this possible. Note also that it is only possible to rotation-normalize the axis target after  
5 it has had the ring's normalizations applied, since the perspective distortion can hide the axis target's axis. The axis target's original rotation provides a useful approximation of the tag's rotation due to pen yaw 29.

The four perspective target structures 17 are the last to be located (at 30). Good estimates of their positions are computed based on their known spatial relationships to  
10 the ring and axis targets, the aspect and rotation of the ring, and the rotation of the axis. Matching proceeds by applying the ring's normalizations to each shape's moments. Once their second-order moments are normalized the circular perspective targets are easy to recognize, and the target closest to each estimated position is taken as a match. The original centroids of the four perspective targets are then taken to be the perspective-  
15 distorted corners 31 of a square of known size in tag space, and an eight-degree-of-freedom perspective transform 33 is inferred (at 32) based on solving the well-understood equations relating the four tag-space and image-space point pairs.

The inferred tag-space to image-space perspective transform is used to project  
(at 36) each known data bit position in tag space into image space where the real-valued  
20 position is used to bilinearly interpolate (at 36) the four relevant adjacent pixels in the input image. The previously computed image threshold 21 is used to threshold the result to produce the final bit value 37.

Once all 360 data bits 37 have been obtained in this way, each of the six 60-bit Reed-Solomon codewords is decoded (at 38) to yield 20 decoded bits 39, or 120 decoded  
25 bits in total. Note that the codeword symbols are sampled in codeword order, so that codewords are implicitly de-interleaved during the sampling process.

The ring target 15 is only sought in a subarea of the image whose relationship to the image guarantees that the ring, if found, is part of a complete tag. If a complete tag is not found and successfully decoded, then no pen position is recorded for the current  
30 frame. Given adequate processing power and ideally a non-minimal field of view 193, an alternative strategy involves seeking another tag in the current image.

The obtained tag data indicates the identity of the region containing the tag and the position of the tag within the region. An accurate position 35 of the pen nib in the region, as well as the overall orientation 35 of the pen, is then inferred (at 34) from the perspective transform 33 observed on the tag and the known spatial relationship between  
5 the pen's physical axis and the pen's optical axis.

### 1.2.5 Tag Map

Decoding a tag results in a region ID, a tag ID, and a tag-relative pen transform. Before the tag ID and the tag-relative pen location can be translated into an absolute location within the tagged region, the location of the tag within the region must be  
10 known. This is given by a tag map, a function which maps each tag ID in a tagged region to a corresponding location. The tag map class diagram is shown in Figure 22, as part of the netpage printer class diagram.

A tag map reflects the scheme used to tile the surface region with tags, and this can vary according to surface type. When multiple tagged regions share the same tiling  
15 scheme and the same tag numbering scheme, they can also share the same tag map.

The tag map for a region must be retrievable via the region ID. Thus, given a region ID, a tag ID and a pen transform, the tag map can be retrieved, the tag ID can be translated into an absolute tag location within the region, and the tag-relative pen location can be added to the tag location to yield an absolute pen location within the  
20 region.

### 1.2.6 Tagging Schemes

Two distinct surface coding schemes are of interest, both of which use the tag structure described earlier in this section. The preferred coding scheme uses "location-  
25 indicating" tags as already discussed. An alternative coding scheme uses object-  
indicating tags.

A location-indicating tag contains a tag ID which, when translated through the tag map associated with the tagged region, yields a unique tag location within the region. The tag-relative location of the pen is added to this tag location to yield the location of the pen within the region. This in turn is used to determine the location of the pen  
30 relative to a user interface element in the page description associated with the region.

Not only is the user interface element itself identified, but a location relative to the user interface element is identified. Location-indicating tags therefore trivially support the capture of an absolute pen path in the zone of a particular user interface element.

5 An object-indicating tag contains a tag ID which directly identifies a user interface element in the page description associated with the region. All the tags in the zone of the user interface element identify the user interface element, making them all identical and therefore indistinguishable. Object-indicating tags do not, therefore, support the capture of an absolute pen path. They do, however, support the capture of a relative pen path. So long as the position sampling frequency exceeds twice the  
10 encountered tag frequency, the displacement from one sampled pen position to the next within a stroke can be unambiguously determined.

Assume a sampling wavelength of  $\lambda_S$  and a tag wavelength of  $\lambda_T$ , with a relationship as defined in **EQ 38**. For two adjacent position samples  $P_i$  and  $P_{i+1}$ , one of **EQ 39** and **EQ 40** will hold.

15 Assuming both equations hold leads to the relationship defined in **EQ 41**.

Since **EQ 41** contradicts **EQ 38**, the assumption that both **EQ 39** and **EQ 40** hold must be incorrect, and the choice is therefore unambiguous, as stated.

The illustration in Figure 60 shows four tags 500 and a one-dimensional stroke of six sample positions 582 which satisfy **EQ 38**. Possible aliases 584 of the sample  
20 positions are also shown. From inspection, if the distance from one sample position to the next is  $\lambda_S$ , then the distance from a sample position to the alias of the next sample position exceeds  $\lambda_S$ .

If the tag wavelength  $\lambda_T$  is 4.7 mm, as discussed in earlier, then the sampling wavelength  $\lambda_S$  must be less than 2.35 mm. If the temporal sampling frequency is 100 Hz  
25 as required for accurate handwriting recognition, then the pen speed must be less than 235 mm/s to satisfy **EQ 38**.

With either tagging scheme, the tags function in cooperation with associated visual elements on the netpage as user interactive elements in that a user can interact with the printed page using an appropriate sensing device in order for tag data to be read  
30 by the sensing device and for an appropriate response to be generated in the netpage



system.

### 1.3 DOCUMENT AND PAGE DESCRIPTIONS

A preferred embodiment of a document and page description class diagram is shown in Figures 25 and 26.

5 In the netpage system a document is described at three levels. At the most abstract level the document 836 has a hierarchical structure whose terminal elements 839 are associated with content objects 840 such as text objects, text style objects, image objects, etc. Once the document is printed on a printer with a particular page size and according to a particular user's scale factor preference, the document is paginated and  
10 otherwise formatted. Formatted terminal elements 835 will in some cases be associated with content objects which are different from those associated with their corresponding terminal elements, particularly where the content objects are style-related. Each printed instance of a document and page is also described separately, to allow input captured through a particular page instance 830 to be recorded separately from input captured  
15 through other instances of the same page description.

The presence of the most abstract document description on the page server allows a user to request a copy of a document without being forced to accept the source document's specific format. The user may be requesting a copy through a printer with a different page size, for example. Conversely, the presence of the formatted document  
20 description on the page server allows the page server to efficiently interpret user actions on a particular printed page.

A formatted document 834 consists of a set of formatted page descriptions 5, each of which consists of a set of formatted terminal elements 835. Each formatted element has a spatial extent or zone 58 on the page. This defines the active area of input  
25 elements such as hyperlinks and input fields.

A document instance 831 corresponds to a formatted document 834. It consists of a set of page instances 830, each of which corresponds to a page description 5 of the formatted document. Each page instance 830 describes a single unique printed netpage 1, and records the page ID 50 of the netpage. A page instance is not part of a document  
30 instance if it represents a copy of a page requested in isolation.

A page instance consists of a set of terminal element instances 832. An element instance only exists if it records instance-specific information. Thus, a hyperlink instance exists for a hyperlink element because it records a transaction ID 55 which is specific to the page instance, and a field instance exists for a field element because it records input specific to the page instance. An element instance does not exist, however, for static elements such as textflows.

A terminal element can be a static element 843, a hyperlink element 844, a field element 845 or a page server command element 846, as shown in Figure 27. A static element 843 can be a style element 847 with an associated style object 854, a textflow element 848 with an associated styled text object 855, an image element 849 with an associated image element 856, a graphic element 850 with an associated graphic object 857, a video clip element 851 with an associated video clip object 858, an audio clip element 852 with an associated audio clip object 859, or a script element 853 with an associated script object 860, as shown in Figure 28.

A page instance has a background field 833 which is used to record any digital ink captured on the page which does not apply to a specific input element.

In the preferred form of the invention, a tag map 811 is associated with each page instance to allow tags on the page to be translated into locations on the page.

#### **1.4 THE NETPAGE NETWORK**

In a preferred embodiment, a netpage network consists of a distributed set of netpage page servers 10, netpage registration servers 11, netpage ID servers 12, netpage application servers 13, netpage publication servers 14, and netpage printers 601 connected via a network 19 such as the Internet, as shown in Figure 3.

The netpage registration server 11 is a server which records relationships between users, pens, printers, applications and publications, and thereby authorizes various network activities. It authenticates users and acts as a signing proxy on behalf of authenticated users in application transactions. It also provides handwriting recognition services. As described above, a netpage page server 10 maintains persistent information about page descriptions and page instances. The netpage network includes any number of page servers, each handling a subset of page instances. Since a page server also

maintains user input values for each page instance, clients such as netpage printers send netpage input directly to the appropriate page server. The page server interprets any such input relative to the description of the corresponding page.

5 A netpage ID server 12 allocates document IDs 51 on demand, and provides load-balancing of page servers via its ID allocation scheme.

A netpage printer uses the Internet Distributed Name System (DNS), or similar, to resolve a netpage page ID 50 into the network address of the netpage page server handling the corresponding page instance.

10 A netpage application server 13 is a server which hosts interactive netpage applications. A netpage publication server 14 is an application server which publishes netpage documents to netpage printers. They are described in detail in Section 2.

15 Netpage servers can be hosted on a variety of network server platforms from manufacturers such as IBM, Hewlett-Packard, and Sun. Multiple netpage servers can run concurrently on a single host, and a single server can be distributed over a number of hosts. Some or all of the functionality provided by netpage servers, and in particular the functionality provided by the ID server and the page server, can also be provided directly in a netpage appliance such as a netpage printer, in a computer workstation, or on a local network.

## 20 1.5 THE NETPAGE PRINTER

The netpage printer 601 is an appliance which is registered with the netpage system and prints netpage documents on demand and via subscription. Each printer has a unique printer ID 62, and is connected to the netpage network via a network such as the Internet, ideally via a broadband connection.

25 Apart from identity and security settings in non-volatile memory, the netpage printer contains no persistent storage. As far as a user is concerned, "the network is the computer". Netpages function interactively across space and time with the help of the distributed netpage page servers 10, independently of particular netpage printers.

30 The netpage printer receives subscribed netpage documents from netpage publication servers 14. Each document is distributed in two parts: the page layouts, and the actual text and image objects which populate the pages. Because of personalization,

page layouts are typically specific to a particular subscriber and so are pointcast to the subscriber's printer via the appropriate page server. Text and image objects, on the other hand, are typically shared with other subscribers, and so are multicast to all subscribers' printers and the appropriate page servers.

- 5           The netpage publication server optimizes the segmentation of document content into pointcasts and multicasts. After receiving the pointcast of a document's page layouts, the printer knows which multicasts, if any, to listen to.

Once the printer has received the complete page layouts and objects that define the document to be printed, it can print the document.

- 10          The printer rasterizes and prints odd and even pages simultaneously on both sides of the sheet. It contains duplexed print engine controllers 760 and print engines utilizing Memjet™ printheads 350 for this purpose.

- The printing process consists of two decoupled stages: rasterization of page descriptions, and expansion and printing of page images. The raster image processor  
15 (RIP) consists of one or more standard DSPs 757 running in parallel. The duplexed print engine controllers consist of custom processors which expand, dither and print page images in real time, synchronized with the operation of the printheads in the print engines.

- Printers not enabled for IR printing have the option to print tags using IR-  
20 absorptive black ink, although this restricts tags to otherwise empty areas of the page. Although such pages have more limited functionality than IR-printed pages, they are still classed as netpages.

- A normal netpage printer prints netpages on sheets of paper. More specialised netpage printers may print onto more specialised surfaces, such as globes. Each printer  
25 supports at least one surface type, and supports at least one tag tiling scheme, and hence tag map, for each surface type. The tag map 811 which describes the tag tiling scheme actually used to print a document becomes associated with that document so that the document's tags can be correctly interpreted.

- Figure 2 shows the netpage printer class diagram, reflecting printer-related  
30 information maintained by a registration server 11 on the netpage network.

A preferred embodiment of the netpage printer is described in greater detail in Section 6 below, with reference to Figures 11 to 16.

### 1.5.1 Memjet™ Printheads

The netpage system can operate using printers made with a wide range of digital printing technologies, including thermal inkjet, piezoelectric inkjet, laser electrophotographic, and others. However, for wide consumer acceptance, it is desirable that a netpage printer have the following characteristics:

- photographic quality color printing
- high quality text printing
- high reliability
- low printer cost
- low ink cost
- low paper cost
- simple operation
- nearly silent printing
- high printing speed
- simultaneous double sided printing
- compact form factor
- low power consumption

No commercially available printing technology has all of these characteristics.

To enable to production of printers with these characteristics, the present applicant has invented a new print technology, referred to as Memjet™ technology. Memjet™ is a drop-on-demand inkjet technology that incorporates pagewidth printheads fabricated using microelectromechanical systems (MEMS) technology. Figure 17 shows a single printing element 300 of a Memjet™ printhead. The netpage wallprinter incorporates 168960 printing elements 300 to form a 1600 dpi pagewidth duplex printer. This printer simultaneously prints cyan, magenta, yellow, black, and infrared inks as well

as paper conditioner and ink fixative.

The printing element 300 is approximately 110 microns long by 32 microns wide. Arrays of these printing elements are formed on a silicon substrate 301 that incorporates CMOS logic, data transfer, timing, and drive circuits (not shown).

5           Major elements of the printing element 300 are the nozzle 302, the nozzle rim 303, the nozzle chamber 304, the fluidic seal 305, the ink channel rim 306, the lever arm 307, the active actuator beam pair 308, the passive actuator beam pair 309, the active actuator anchor 310, the passive actuator anchor 311, and the ink inlet 312.

10           The active actuator beam pair 308 is mechanically joined to the passive actuator beam pair 309 at the join 319. Both beams pairs are anchored at their respective anchor points 310 and 311. The combination of elements 308, 309, 310, 311, and 319 form a cantilevered electrothermal bend actuator 320.

15           Figure 18 shows a small part of an array of printing elements 300, including a cross section 315 of a printing element 300. The cross section 315 is shown without ink, to clearly show the ink inlet 312 that passes through the silicon wafer 301.

          Figures 19(a), 19(b) and 19(c) show the operating cycle of a Memjet™ printing element 300.

20           Figure 19(a) shows the quiescent position of the ink meniscus 316 prior to printing an ink droplet. Ink is retained in the nozzle chamber by surface tension at the ink meniscus 316 and at the fluidic seal 305 formed between the nozzle chamber 304 and the ink channel rim 306.

25           While printing, the printhead CMOS circuitry distributes data from the print engine controller to the correct printing element, latches the data, and buffers the data to drive the electrodes 318 of the active actuator beam pair 308. This causes an electrical current to pass through the beam pair 308 for about one microsecond, resulting in Joule heating. The temperature increase resulting from Joule heating causes the beam pair 308 to expand. As the passive actuator beam pair 309 is not heated, it does not expand, resulting in a stress difference between the two beam pairs. This stress difference is partially resolved by the cantilevered end of the electrothermal bend actuator 320  
30           bending towards the substrate 301. The lever arm 307 transmits this movement to the

nozzle chamber 304. The nozzle chamber 304 moves about two microns to the position shown in Figure 19(b). This increases the ink pressure, forcing ink 321 out of the nozzle 302, and causing the ink meniscus 316 to bulge. The nozzle rim 303 prevents the ink meniscus 316 from spreading across the surface of the nozzle chamber 304.

5           As the temperature of the beam pairs 308 and 309 equalizes, the actuator 320 returns to its original position. This aids in the break-off of the ink droplet 317 from the ink 321 in the nozzle chamber, as shown in Figure 19(c). The nozzle chamber is refilled by the action of the surface tension at the meniscus 316.

10           Figure 20 shows a segment of a printhead 350. In a netpage printer, the length of the printhead is the full width of the paper (typically 210 mm) in the direction 351. The segment shown is 0.4 mm long (about 0.2% of a complete printhead). When printing, the paper is moved past the fixed printhead in the direction 352. The printhead has 6 rows of interdigitated printing elements 300, printing the six colors or types of ink supplied by the ink inlets 312.

15           To protect the fragile surface of the printhead during operation, a nozzle guard wafer 330 is attached to the printhead substrate 301. For each nozzle 302 there is a corresponding nozzle guard hole 331 through which the ink droplets are fired. To prevent the nozzle guard holes 331 from becoming blocked by paper fibers or other debris, filtered air is pumped through the air inlets 332 and out of the nozzle guard holes during  
20           printing. To prevent ink 321 from drying, the nozzle guard is sealed while the printer is idle.

## **1.6       The Netpage Pen**

25           The active sensing device of the netpage system is typically a pen 101, which, using its embedded controller 134, is able to capture and decode IR position tags from a page via an image sensor. The image sensor is a solid-state device provided with an appropriate filter to permit sensing at only near-infrared wavelengths. As described in more detail below, the system is able to sense when the nib is in contact with the surface, and the pen is able to sense tags at a sufficient rate to capture human handwriting (i.e. at 200 dpi or greater and 100 Hz or faster). Information captured by the pen is encrypted  
30           and wirelessly transmitted to the printer (or base station), the printer or base station interpreting the data with respect to the (known) page structure.

The preferred embodiment of the netpage pen operates both as a normal marking ink pen and as a non-marking stylus. The marking aspect, however, is not necessary for using the netpage system as a browsing system, such as when it is used as an Internet interface. Each netpage pen is registered with the netpage system and has a  
5 unique pen ID 61. Figure 23 shows the netpage pen class diagram, reflecting pen-related information maintained by a registration server 11 on the netpage network.

When either nib is in contact with a netpage, the pen determines its position and orientation relative to the page. The nib is attached to a force sensor, and the force on the nib is interpreted relative to a threshold to indicate whether the pen is “up” or  
10 “down”. This allows a interactive element on the page to be ‘clicked’ by pressing with the pen nib, in order to request, say, information from a network. Furthermore, the force is captured as a continuous value to allow, say, the full dynamics of a signature to be verified.

The pen determines the position and orientation of its nib on the netpage by  
15 imaging, in the infrared spectrum, an area 193 of the page in the vicinity of the nib. It decodes the nearest tag and computes the position of the nib relative to the tag from the observed perspective distortion on the imaged tag and the known geometry of the pen optics. Although the position resolution of the tag may be low, because the tag density on the page is inversely proportional to the tag size, the adjusted position resolution is  
20 quite high, exceeding the minimum resolution required for accurate handwriting recognition.

Pen actions relative to a netpage are captured as a series of strokes. A stroke consists of a sequence of time-stamped pen positions on the page, initiated by a pen-down event and completed by the subsequent pen-up event. A stroke is also tagged with  
25 the page ID 50 of the netpage whenever the page ID changes, which, under normal circumstances, is at the commencement of the stroke.

Each netpage pen has a current selection 826 associated with it, allowing the user to perform copy and paste operations etc. The selection is timestamped to allow the system to discard it after a defined time period. The current selection describes a region  
30 of a page instance. It consists of the most recent digital ink stroke captured through the pen relative to the background area of the page. It is interpreted in an application-specific



manner once it is submitted to an application via a selection hyperlink activation.

Each pen has a current nib 824. This is the nib last notified by the pen to the system. In the case of the default netpage pen described above, either the marking black ink nib or the non-marking stylus nib is current. Each pen also has a current nib style 5 825. This is the nib style last associated with the pen by an application, e.g. in response to the user selecting a color from a palette. The default nib style is the nib style associated with the current nib. Strokes captured through a pen are tagged with the current nib style. When the strokes are subsequently reproduced, they are reproduced in the nib style with which they are tagged.

10 Whenever the pen is within range of a printer with which it can communicate, the pen slowly flashes its "online" LED. When the pen fails to decode a stroke relative to the page, it momentarily activates its "error" LED. When the pen succeeds in decoding a stroke relative to the page, it momentarily activates its "ok" LED.

A sequence of captured strokes is referred to as digital ink. Digital ink forms 15 the basis for the digital exchange of drawings and handwriting, for online recognition of handwriting, and for online verification of signatures.

The pen is wireless and transmits digital ink to the netpage printer via a short-range radio link. The transmitted digital ink is encrypted for privacy and security and packetized for efficient transmission, but is always flushed on a pen-up event to ensure 20 timely handling in the printer.

When the pen is out-of-range of a printer it buffers digital ink in internal memory, which has a capacity of over ten minutes of continuous handwriting. When the pen is once again within range of a printer, it transfers any buffered digital ink.

A pen can be registered with any number of printers, but because all state data 25 resides in netpages both on paper and on the network, it is largely immaterial which printer a pen is communicating with at any particular time.

A preferred embodiment of the pen is described in greater detail in Section 6 below, with reference to Figures 8 to 10.

## 1.7 NETPAGE INTERACTION

30 The netpage printer 601 receives data relating to a stroke from the pen 101

when the pen is used to interact with a netpage 1. The coded data 3 of the tags 4 is read by the pen when it is used to execute a movement, such as a stroke. The data allows the identity of the particular page and associated interactive element to be determined and an indication of the relative positioning of the pen relative to the page to be obtained. The  
5 indicating data is transmitted to the printer, where it resolves, via the DNS, the page ID 50 of the stroke into the network address of the netpage page server 10 which maintains the corresponding page instance 830. It then transmits the stroke to the page server. If the page was recently identified in an earlier stroke, then the printer may already have the address of the relevant page server in its cache. Each netpage consists of a compact page  
10 layout maintained persistently by a netpage page server (see below). The page layout refers to objects such as images, fonts and pieces of text, typically stored elsewhere on the netpage network.

When the page server receives the stroke from the pen, it retrieves the page description to which the stroke applies, and determines which element of the page  
15 description the stroke intersects. It is then able to interpret the stroke in the context of the type of the relevant element.

A “click” is a stroke where the distance and time between the pen down position and the subsequent pen up position are both less than some small maximum. An object which is activated by a click typically requires a click to be activated, and  
20 accordingly, a longer stroke is ignored. The failure of a pen action, such as a “sloppy” click, to register is indicated by the lack of response from the pen’s “ok” LED.

There are two kinds of input elements in a netpage page description: hyperlinks and form fields. Input through a form field can also trigger the activation of an associated hyperlink.

### 25 1.7.1 Hyperlinks

A hyperlink is a means of sending a message to a remote application, and typically elicits a printed response in the netpage system.

A hyperlink element 844 identifies the application 71 which handles activation of the hyperlink, a link ID 54 which identifies the hyperlink to the application, an “alias  
30 required” flag which asks the system to include the user’s application alias ID 65 in the

hyperlink activation, and a description which is used when the hyperlink is recorded as a favorite or appears in the user's history. The hyperlink element class diagram is shown in Figure 29.

When a hyperlink is activated, the page server sends a request to an application  
5 somewhere on the network. The application is identified by an application ID 64, and the application ID is resolved in the normal way via the DNS. There are three types of hyperlinks: general hyperlinks 863, form hyperlinks 865, and selection hyperlinks 864, as shown in Figure 30. A general hyperlink can implement a request for a linked document, or may simply signal a preference to a server. A form hyperlink submits the  
10 corresponding form to the application. A selection hyperlink submits the current selection to the application. If the current selection contains a single-word piece of text, for example, the application may return a single-page document giving the word's meaning within the context in which it appears, or a translation into a different language. Each hyperlink type is characterized by what information is submitted to the application.

15 The corresponding hyperlink instance 862 records a transaction ID 55 which can be specific to the page instance on which the hyperlink instance appears. The transaction ID can identify user-specific data to the application, for example a "shopping cart" of pending purchases maintained by a purchasing application on behalf of the user.

The system includes the pen's current selection 826 in a selection hyperlink  
20 activation. The system includes the content of the associated form instance 868 in a form hyperlink activation, although if the hyperlink has its "submit delta" attribute set, only input since the last form submission is included. The system includes an effective return path in all hyperlink activations.

A hyperlinked group 866 is a group element 838 which has an associated  
25 hyperlink, as shown in Figure 31. When input occurs through any field element in the group, the hyperlink 844 associated with the group is activated. A hyperlinked group can be used to associate hyperlink behavior with a field such as a checkbox. It can also be used, in conjunction with the "submit delta" attribute of a form hyperlink, to provide continuous input to an application. It can therefore be used to support a "blackboard"  
30 interaction model, i.e. where input is captured and therefore shared as soon as it occurs.

### 1.7.2 Forms

A form defines a collection of related input fields used to capture a related set of inputs through a printed netpage. A form allows a user to submit one or more parameters to an application software program running on a server.

5           A form 867 is a group element 838 in the document hierarchy. It ultimately contains a set of terminal field elements 839. A form instance 868 represents a printed instance of a form. It consists of a set of field instances 870 which correspond to the field elements 845 of the form. Each field instance has an associated value 871, whose type depends on the type of the corresponding field element. Each field value records input  
10 through a particular printed form instance, i.e. through one or more printed netpages. The form class diagram is shown in Figure 32.

Each form instance has a status 872 which indicates whether the form is active, frozen, submitted, void or expired. A form is active when first printed. A form becomes frozen once it is signed. A form becomes submitted once one of its submission  
15 hyperlinks has been activated, unless the hyperlink has its “submit delta” attribute set. A form becomes void when the user invokes a void form, reset form or duplicate form page command. A form expires when the time the form has been active exceeds the form’s specified lifetime. While the form is active, form input is allowed. Input through a form which is not active is instead captured in the background field 833 of the relevant page  
20 instance. When the form is active or frozen, form submission is allowed. Any attempt to submit a form when the form is not active or frozen is rejected, and instead elicits an form status report.

Each form instance is associated (at 59) with any form instances derived from it, thus providing a version history. This allows all but the latest version of a form in a  
25 particular time period to be excluded from a search.

All input is captured as digital ink. Digital ink 873 consists of a set of timestamped stroke groups 874, each of which consists of a set of styled strokes 875. Each stroke consists of a set of timestamped pen positions 876, each of which also includes pen orientation and nib force. The digital ink class diagram is shown in Figure  
30 33.

A field element 845 can be a checkbox field 877, a text field 878, a drawing

field 879, or a signature field 880. The field element class diagram is shown in Figure 34. Any digital ink captured in a field's zone 58 is assigned to the field.

A checkbox field has an associated boolean value 881, as shown in Figure 35. Any mark (a tick, a cross, a stroke, a fill zigzag, etc.) captured in a checkbox field's zone 5 causes a true value to be assigned to the field's value.

A text field has an associated text value 882, as shown in Figure 36. Any digital ink captured in a text field's zone is automatically converted to text via online handwriting recognition, and the text is assigned to the field's value. Online handwriting recognition is well-understood (see for example Tappert, C., C.Y. Suen and T. Wakahara, "The State of the Art in On-Line Handwriting Recognition", IEEE Transactions on Pattern Analysis and Machine Intelligence, Vol.12, No.8, August 1990). 10

A signature field has an associated digital signature value 883, as shown in Figure 37. Any digital ink captured in a signature field's zone is automatically verified with respect to the identity of the owner of the pen, and a digital signature of the content 15 of the form of which the field is part is generated and assigned to the field's value. The digital signature is generated using the pen user's private signature key specific to the application which owns the form. Online signature verification is well-understood (see for example Plamondon, R. and G. Lorette, "Automatic Signature Verification and Writer Identification – The State of the Art", Pattern Recognition, Vol.22, No.2, 1989).

A field element is hidden if its "hidden" attribute is set. A hidden field element 20 does not have an input zone on a page and does not accept input. It can have an associated field value which is included in the form data when the form containing the field is submitted.

"Editing" commands, such as strike-throughs indicating deletion, can also be 25 recognized in form fields.

Because the handwriting recognition algorithm works "online" (i.e. with access to the dynamics of the pen movement), rather than "offline" (i.e. with access only to a bitmap of pen markings), it can recognize run-on discretely-written characters with relatively high accuracy, without a writer-dependent training phase. A writer-dependent 30 model of handwriting is automatically generated over time, however, and can be

generated up-front if necessary,

Digital ink, as already stated, consists of a sequence of strokes. Any stroke which starts in a particular element's zone is appended to that element's digital ink stream, ready for interpretation. Any stroke not appended to an object's digital ink stream is appended to the background field's digital ink stream.

Digital ink captured in the background field is interpreted as a selection gesture. Circumscription of one or more objects is generally interpreted as a selection of the circumscribed objects, although the actual interpretation is application-specific.

Table 2 summarises these various pen interactions with a netpage.

**Table 2. Summary of pen interactions with a netpage**

Object	Type	Pen input	Action
Hyperlink	General	Click	Submit action to application
	Form	Click	Submit form to application
	Selection	Click	Submit selection to application
Form field	Checkbox	Any mark	Assign true to field
	Text	Handwriting	Convert digital ink to text; assign text to field
	Drawing	Digital ink	Assign digital ink to field
	Signature	Signature	Verify digital ink signature; generate digital signature of form; assign digital signature to field
None	-	Circumscription	Assign digital ink to current selection

The system maintains a current selection for each pen. The selection consists simply of the most recent stroke captured in the background field. The selection is cleared after an inactivity timeout to ensure predictable behavior.

The raw digital ink captured in every field is retained on the netpage page server and is optionally transmitted with the form data when the form is submitted to the application. This allows the application to interrogate the raw digital ink should it suspect the original conversion, such as the conversion of handwritten text. This can, for example, involve human intervention at the application level for forms which fail certain application-specific consistency checks. As an extension to this, the entire background

area of a form can be designated as a drawing field. The application can then decide, on the basis of the presence of digital ink outside the explicit fields of the form, to route the form to a human operator, on the assumption that the user may have indicated amendments to the filled-in fields outside of those fields.

5           Figure 38 shows a flowchart of the process of handling pen input relative to a netpage. The process consists of receiving (at 884) a stroke from the pen; identifying (at 885) the page instance 830 to which the page ID 50 in the stroke refers; retrieving (at 886) the page description 5; identifying (at 887) a formatted element 839 whose zone 58 the stroke intersects; determining (at 888) whether the formatted element corresponds to  
10 a field element, and if so appending (at 892) the received stroke to the digital ink of the field value 871, interpreting (at 893) the accumulated digital ink of the field, and determining (at 894) whether the field is part of a hyperlinked group 866 and if so activating (at 895) the associated hyperlink; alternatively determining (at 889) whether the formatted element corresponds to a hyperlink element and if so activating (at 895)  
15 the corresponding hyperlink; alternatively, in the absence of an input field or hyperlink, appending (at 890) the received stroke to the digital ink of the background field 833; and copying (at 891) the received stroke to the current selection 826 of the current pen, as maintained by the registration server.

Figure 38a shows a detailed flowchart of step 893 in the process shown in  
20 Figure 38, where the accumulated digital ink of a field is interpreted according to the type of the field. The process consists of determining (at 896) whether the field is a checkbox and (at 897) whether the digital ink represents a checkmark, and if so assigning (at 898) a true value to the field value; alternatively determining (at 899) whether the field is a text field and if so converting (at 900) the digital ink to computer  
25 text, with the help of the appropriate registration server, and assigning (at 901) the converted computer text to the field value; alternatively determining (at 902) whether the field is a signature field and if so verifying (at 903) the digital ink as the signature of the pen's owner, with the help of the appropriate registration server, creating (at 904) a digital signature of the contents of the corresponding form, also with the help of the  
30 registration server and using the pen owner's private signature key relating to the corresponding application, and assigning (at 905) the digital signature to the field value.

### 1.7.3 Page Server Commands

A page server command is a command which is handled locally by the page server. It operates directly on form, page and document instances.

5 A page server command 907 can be a void form command 908, a duplicate form command 909, a reset form command 910, a get form status command 911, a duplicate page command 912, a reset page command 913, a get page status command 914, a duplicate document command 915, a reset document command 916, or a get document status command 917, as shown in Figure 39.

10 A void form command voids the corresponding form instance. A duplicate form command voids the corresponding form instance and then produces an active printed copy of the current form instance with field values preserved. The copy contains the same hyperlink transaction IDs as the original, and so is indistinguishable from the original to an application. A reset form command voids the corresponding form instance and then produces an active printed copy of the form instance with field values  
15 discarded. A get form status command produces a printed report on the status of the corresponding form instance, including who published it, when it was printed, for whom it was printed, and the form status of the form instance.

Since a form hyperlink instance contains a transaction ID, the application has to be involved in producing a new form instance. A button requesting a new form instance  
20 is therefore typically implemented as a hyperlink.

A duplicate page command produces a printed copy of the corresponding page instance with the background field value preserved. If the page contains a form or is part of a form, then the duplicate page command is interpreted as a duplicate form command. A reset page command produces a printed copy of the corresponding page instance with  
25 the background field value discarded. If the page contains a form or is part of a form, then the reset page command is interpreted as a reset form command. A get page status command produces a printed report on the status of the corresponding page instance, including who published it, when it was printed, for whom it was printed, and the status of any forms it contains or is part of.

30 The netpage logo which appears on every netpage is usually associated with a duplicate page element.



When a page instance is duplicated with field values preserved, field values are printed in their native form, i.e. a checkmark appears as a standard checkmark graphic, and text appears as typeset text. Only drawings and signatures appear in their original form, with a signature accompanied by a standard graphic indicating successful signature verification.

A duplicate document command produces a printed copy of the corresponding document instance with background field values preserved. If the document contains any forms, then the duplicate document command duplicates the forms in the same way a duplicate form command does. A reset document command produces a printed copy of the corresponding document instance with background field values discarded. If the document contains any forms, then the reset document command resets the forms in the same way a reset form command does. A get document status command produces a printed report on the status of the corresponding document instance, including who published it, when it was printed, for whom it was printed, and the status of any forms it contains.

If the page server command's "on selected" attribute is set, then the command operates on the page identified by the pen's current selection rather than on the page containing the command. This allows a menu of page server commands to be printed. If the target page doesn't contain a page server command element for the designated page server command, then the command is ignored.

An application can provide application-specific handling by embedding the relevant page server command element in a hyperlinked group. The page server activates the hyperlink associated with the hyperlinked group rather than executing the page server command.

A page server command element is hidden if its "hidden" attribute is set. A hidden command element does not have an input zone on a page and so cannot be activated directly by a user. It can, however, be activated via a page server command embedded in a different page, if that page server command has its "on selected" attribute set.

## 1.8 STANDARD FEATURES OF NETPAGES

In the preferred form, each netpage is printed with the netpage logo at the bottom to indicate that it is a netpage and therefore has interactive properties. The logo also acts as a copy button. In most cases pressing the logo produces a copy of the page.

- 5 In the case of a form, the button produces a copy of the entire form. And in the case of a secure document, such as a ticket or coupon, the button elicits an explanatory note or advertising page.

The default single-page copy function is handled directly by the relevant netpage page server. Special copy functions are handled by linking the logo button to an application.

10

## 1.9 USER HELP SYSTEM

In a preferred embodiment, the netpage printer has a single button labelled "Help". When pressed it elicits a single page of information, including:

- status of printer connection
- 15 • status of printer consumables
- top-level help menu
- document function menu
- top-level netpage network directory

The help menu provides a hierarchical manual on how to use the netpage system.

20

The document function menu includes the following functions:

- print a copy of a document
- print a clean copy of a form
- print the status of a document

25 A document function is initiated by simply pressing the button and then touching any page of the document. The status of a document indicates who published it and when, to whom it was delivered, and to whom and when it was subsequently submitted as a form.

The netpage network directory allows the user to navigate the hierarchy of publications and services on the network. As an alternative, the user can call the netpage network “900” number “yellow pages” and speak to a human operator. The operator can locate the desired document and route it to the user’s printer. Depending on the  
5 document type, the publisher or the user pays the small “yellow pages” service fee.

The help page is obviously unavailable if the printer is unable to print. In this case the “error” light is lit and the user can request remote diagnosis over the network.

## **2 PERSONALIZED PUBLICATION MODEL**

In the following description, news is used as a canonical publication example  
10 to illustrate personalization mechanisms in the netpage system. Although news is often used in the limited sense of newspaper and newsmagazine news, the intended scope in the present context is wider.

In the netpage system, the editorial content and the advertising content of a news publication are personalized using different mechanisms. The editorial content is  
15 personalized according to the reader’s explicitly stated and implicitly captured interest profile. The advertising content is personalized according to the reader’s locality and demographic.

### **2.1 EDITORIAL PERSONALIZATION**

A subscriber can draw on two kinds of news sources: those that deliver news  
20 publications, and those that deliver news streams. While news publications are aggregated and edited by the publisher, news streams are aggregated either by a news publisher or by a specialized news aggregator. News publications typically correspond to traditional newspapers and newsmagazines, while news streams can be many and varied: a “raw” news feed from a news service, a cartoon strip, a freelance writer’s column, a  
25 friend’s bulletin board, or the reader’s own e-mail.

The netpage publication server supports the publication of edited news publications as well as the aggregation of multiple news streams. By handling the aggregation and hence the formatting of news streams selected directly by the reader, the server is able to place advertising on pages over which it otherwise has no editorial  
30 control.

The subscriber builds a daily newspaper by selecting one or more contributing news publications, and creating a personalized version of each. The resulting daily editions are printed and bound together into a single newspaper. The various members of a household typically express their different interests and tastes by selecting different  
5 daily publications and then customizing them.

For each publication, the reader optionally selects specific sections. Some sections appear daily, while others appear weekly. The daily sections available from The New York Times online, for example, include “Page One Plus”, “National”, “International”, “Opinion”, “Business”, “Arts/Living”, “Technology”, and “Sports”. The  
10 set of available sections is specific to a publication, as is the default subset.

The reader can extend the daily newspaper by creating custom sections, each one drawing on any number of news streams. Custom sections might be created for e-mail and friends’ announcements (“Personal”), or for monitoring news feeds for specific topics (“Alerts” or “Clippings”).

15 For each section, the reader optionally specifies its size, either qualitatively (e.g. short, medium, or long), or numerically (i.e. as a limit on its number of pages), and the desired proportion of advertising, either qualitatively (e.g. high, normal, low, none), or numerically (i.e. as a percentage).

The reader also optionally expresses a preference for a large number of shorter  
20 articles or a small number of longer articles. Each article is ideally written (or edited) in both short and long forms to support this preference.

An article may also be written (or edited) in different versions to match the expected sophistication of the reader, for example to provide children’s and adults’ versions. The appropriate version is selected according to the reader’s age. The reader  
25 can specify a “reading age” which takes precedence over their biological age.

The articles which make up each section are selected and prioritized by the editors, and each is assigned a useful lifetime. By default they are delivered to all relevant subscribers, in priority order, subject to space constraints in the subscribers’ editions.

30 In sections where it is appropriate, the reader may optionally enable

collaborative filtering. This is then applied to articles which have a sufficiently long lifetime. Each article which qualifies for collaborative filtering is printed with rating buttons at the end of the article. The buttons can provide an easy choice (e.g. “liked” and “disliked”), making it more likely that readers will bother to rate the article.

- 5           Articles with high priorities and short lifetimes are therefore effectively considered essential reading by the editors and are delivered to most relevant subscribers.

- 10           The reader optionally specifies a serendipity factor, either qualitatively (e.g. do or don’t surprise me), or numerically. A high serendipity factor lowers the threshold used for matching during collaborative filtering. A high factor makes it more likely that the corresponding section will be filled to the reader’s specified capacity. A different serendipity factor can be specified for different days of the week.

The reader also optionally specifies topics of particular interest within a section, and this modifies the priorities assigned by the editors.

- 15           The speed of the reader’s Internet connection affects the quality at which images can be delivered. The reader optionally specifies a preference for fewer images or smaller images or both. If the number or size of images is not reduced, then images may be delivered at lower quality (i.e. at lower resolution or with greater compression).

- 20           At a global level, the reader specifies how quantities, dates, times and monetary values are localized. This involves specifying whether units are imperial or metric, a local timezone and time format, and a local currency, and whether the localization consist of *in situ* translation or annotation. These preferences are derived from the reader’s locality by default.

- 25           To reduce reading difficulties caused by poor eyesight, the reader optionally specifies a global preference for a larger presentation. Both text and images are scaled accordingly, and less information is accommodated on each page.

- 30           The language in which a news publication is published, and its corresponding text encoding, is a property of the publication and not a preference expressed by the user. However, the netpage system can be configured to provide automatic translation services in various guises.

## 2.2 ADVERTISING LOCALIZATION AND TARGETING

The personalization of the editorial content directly affects the advertising content, because advertising is typically placed to exploit the editorial context. Travel ads, for example, are more likely to appear in a travel section than elsewhere. The value of the editorial content to an advertiser (and therefore to the publisher) lies in its ability to attract large numbers of readers with the right demographics.

Effective advertising is placed on the basis of locality and demographics. Locality determines proximity to particular services, retailers etc., and particular interests and concerns associated with the local community and environment. Demographics determine general interests and preoccupations as well as likely spending patterns.

A news publisher's most profitable product is advertising "space", a multi-dimensional entity determined by the publication's geographic coverage, the size of its readership, its readership demographics, and the page area available for advertising.

In the netpage system, the netpage publication server computes the approximate multi-dimensional size of a publication's saleable advertising space on a per-section basis, taking into account the publication's geographic coverage, the section's readership, the size of each reader's section edition, each reader's advertising proportion, and each reader's demographic.

In comparison with other media, the netpage system allows the advertising space to be defined in greater detail, and allows smaller pieces of it to be sold separately. It therefore allows it to be sold at closer to its true value.

For example, the same advertising "slot" can be sold in varying proportions to several advertisers, with individual readers' pages randomly receiving the advertisement of one advertiser or another, overall preserving the proportion of space sold to each advertiser.

The netpage system allows advertising to be linked directly to detailed product information and online purchasing. It therefore raises the intrinsic value of the advertising space.

Because personalization and localization are handled automatically by netpage publication servers, an advertising aggregator can provide arbitrarily broad coverage of

both geography and demographics. The subsequent disaggregation is efficient because it is automatic. This makes it more cost-effective for publishers to deal with advertising aggregators than to directly capture advertising. Even though the advertising aggregator is taking a proportion of advertising revenue, publishers may find the change profit-  
5 neutral because of the greater efficiency of aggregation. The advertising aggregator acts as an intermediary between advertisers and publishers, and may place the same advertisement in multiple publications.

It is worth noting that ad placement in a netpage publication can be more complex than ad placement in the publication's traditional counterpart, because the  
10 publication's advertising space is more complex. While ignoring the full complexities of negotiations between advertisers, advertising aggregators and publishers, the preferred form of the netpage system provides some automated support for these negotiations, including support for automated auctions of advertising space. Automation is particularly desirable for the placement of advertisements which generate small amounts of income,  
15 such as small or highly localized advertisements.

Once placement has been negotiated, the aggregator captures and edits the advertisement and records it on a netpage ad server. Correspondingly, the publisher records the ad placement on the relevant netpage publication server. When the netpage publication server lays out each user's personalized publication, it picks the relevant  
20 advertisements from the netpage ad server.

## **2.3 USER PROFILES**

### **2.3.1 Information Filtering**

The personalization of news and other publications relies on an assortment of user-specific profile information, including:

- 25
- publication customizations
  - collaborative filtering vectors
  - contact details
  - presentation preferences

The customization of a publication is typically publication-specific, and so the

customization information is maintained by the relevant netpage publication server.

5 A collaborative filtering vector consists of the user's ratings of a number of news items. It is used to correlate different users' interests for the purposes of making recommendations. Although there are benefits to maintaining a single collaborative  
10 filtering vector independently of any particular publication, there are two reasons why it is more practical to maintain a separate vector for each publication: there is likely to be more overlap between the vectors of subscribers to the same publication than between those of subscribers to different publications; and a publication is likely to want to present its users' collaborative filtering vectors as part of the value of its brand, not to be  
15 found elsewhere. Collaborative filtering vectors are therefore also maintained by the relevant netpage publication server.

Contact details, including name, street address, ZIP Code, state, country, telephone numbers, are global by nature, and are maintained by a netpage registration server.

15 Presentation preferences, including those for quantities, dates and times, are likewise global and maintained in the same way.

The localization of advertising relies on the locality indicated in the user's contact details, while the targeting of advertising relies on personal information such as date of birth, gender, marital status, income, profession, education, or qualitative  
20 derivatives such as age range and income range.

For those users who choose to reveal personal information for advertising purposes, the information is maintained by the relevant netpage registration server. In the absence of such information, advertising can be targeted on the basis of the demographic associated with the user's ZIP or ZIP+4 Code.

25 Each user, pen, printer, application provider and application is assigned its own unique identifier, and the netpage registration server maintains the relationships between them, as shown in Figures 21, 22, 23 and 24. For registration purposes, a publisher is a special kind of application provider, and a publication is a special kind of application.

Each user 800 may be authorized to use any number of printers 802, and each  
30 printer may allow any number of users to use it. Each user has a single default printer (at



66), to which periodical publications are delivered by default, whilst pages printed on demand are delivered to the printer through which the user is interacting. The server keeps track of which publishers a user has authorized to print to the user's default printer. A publisher does not record the ID of any particular printer, but instead resolves  
5 the ID when it is required.

When a user subscribes 808 to a publication 807, the publisher 806 (i.e. application provider 803) is authorized to print to a specified printer or the user's default printer. This authorization can be revoked at any time by the user. Each user may have several pens 801, but a pen is specific to a single user. If a user is authorized to use a  
10 particular printer, then that printer recognizes any of the user's pens.

The pen ID is used to locate the corresponding user profile maintained by a particular netpage registration server, via the DNS in the usual way.

A Web terminal 809 can be authorized to print on a particular netpage printer, allowing Web pages and netpage documents encountered during Web browsing to be  
15 conveniently printed on the nearest netpage printer.

The netpage system can collect, on behalf of a printer provider, fees and commissions on income earned through publications printed on the provider's printers. Such income can include advertising fees, click-through fees, e-commerce commissions, and transaction fees. If the printer is owned by the user, then the user is the printer  
20 provider.

Each user also has a netpage account 820 which is used to accumulate micro-debits and credits (such as those described in the preceding paragraph); contact details 815, including name, address and telephone numbers; global preferences 816, including privacy, delivery and localization settings; any number of biometric records 817,  
25 containing the user's encoded signature 818, fingerprint 819 etc; a handwriting model 819 automatically maintained by the system; and SET payment card accounts 821 with which e-commerce payments can be made.

### 2.3.2 Favorites List

A netpage user can maintain a list 922 of "favorites" - links to useful  
30 documents etc. on the netpage network. The list is maintained by the system on the

user's behalf. It is organized as a hierarchy of folders 924, a preferred embodiment of which is shown in the class diagram in Figure 41.

### 2.3.3 History List

5 The system maintains a history list 929 on each user's behalf, containing links to documents etc. accessed by the user through the netpage system. It is organized as a date-ordered list, a preferred embodiment of which is shown in the class diagram in Figure 42.

## 2.4 INTELLIGENT PAGE LAYOUT

10 The netpage publication server automatically lays out the pages of each user's personalized publication on a section-by-section basis. Since most advertisements are in the form of pre-formatted rectangles, they are placed on the page before the editorial content.

15 The advertising ratio for a section can be achieved with wildly varying advertising ratios on individual pages within the section, and the ad layout algorithm exploits this. The algorithm is configured to attempt to co-locate closely tied editorial and advertising content, such as placing ads for roofing material specifically within the publication because of a special feature on do-it-yourself roofing repairs.

The editorial content selected for the user, including text and associated images and graphics, is then laid out according to various aesthetic rules.

20 The entire process, including the selection of ads and the selection of editorial content, must be iterated once the layout has converged, to attempt to more closely achieve the user's stated section size preference. The section size preference can, however, be matched *on average* over time, allowing significant day-to-day variations.

## 2.5 DOCUMENT FORMAT

25 Once the document is laid out, it is encoded for efficient distribution and persistent storage on the netpage network.

The primary efficiency mechanism is the separation of information specific to a single user's edition and information shared between multiple users' editions. The specific information consists of the page layout. The shared information consists of the

objects to which the page layout refers, including images, graphics, and pieces of text.

5 A text object contains fully-formatted text represented in the Extensible Markup Language (XML) using the Extensible Stylesheet Language (XSL). XSL provides precise control over text formatting independently of the region into which the text is being set, which in this case is being provided by the layout. The text object contains embedded language codes to enable automatic translation, and embedded hyphenation hints to aid with paragraph formatting.

10 An image object encodes an image in the JPEG 2000 wavelet-based compressed image format. A graphic object encodes a 2D graphic in Scalable Vector Graphics (SVG) format.

The layout itself consists of a series of placed image and graphic objects, linked textflow objects through which text objects flow, hyperlinks and input fields as described above, and watermark regions. These layout objects are summarized in Table 3. The layout uses a compact format suitable for efficient distribution and storage.

15

**Table 3. Netpage layout objects**

Layout object	Attribute	Format of linked object
Image	Position	-
	Image object ID	JPEG 2000
Graphic	Position	-
	Graphic object ID	SVG
Textflow	Textflow ID	-
	Zone	-
	Optional text object ID	XML/XSL
Hyperlink	Type	-
	Zone	-
	Application ID, etc.	-
Field	Type	-
	Meaning	-
	Zone	-
Watermark	Zone	-

## 2.6 DOCUMENT DISTRIBUTION

As described above, for purposes of efficient distribution and persistent storage

on the netpage network, a user-specific page layout is separated from the shared objects to which it refers.

When a subscribed publication is ready to be distributed, the netpage publication server allocates, with the help of the netpage ID server 12, a unique ID for each page, page instance, document, and document instance.

The server computes a set of optimized subsets of the shared content and creates a multicast channel for each subset, and then tags each user-specific layout with the names of the multicast channels which will carry the shared content used by that layout. The server then pointcasts each user's layouts to that user's printer via the appropriate page server, and when the pointcasting is complete, multicasts the shared content on the specified channels. After receiving its pointcast, each page server and printer subscribes to the multicast channels specified in the page layouts. During the multicasts, each page server and printer extracts from the multicast streams those objects referred to by its page layouts. The page servers persistently archive the received page layouts and shared content.

Once a printer has received all the objects to which its page layouts refer, the printer re-creates the fully-populated layout and then rasterizes and prints it.

Under normal circumstances, the printer prints pages faster than they can be delivered. Assuming a quarter of each page is covered with images, the average page has a size of less than 400KB. The printer can therefore hold in excess of 100 such pages in its internal 64MB memory, allowing for temporary buffers etc. The printer prints at a rate of one page per second. This is equivalent to 400KB or about 3Mbit of page data per second, which is similar to the highest expected rate of page data delivery over a broadband network.

Even under abnormal circumstances, such as when the printer runs out of paper, it is likely that the user will be able to replenish the paper supply before the printer's 100-page internal storage capacity is exhausted.

However, if the printer's internal memory does fill up, then the printer will be unable to make use of a multicast when it first occurs. The netpage publication server therefore allows printers to submit requests for re-multicasts. When a critical number of

requests is received or a timeout occurs, the server re-multicasts the corresponding shared objects.

Once a document is printed, a printer can produce an exact duplicate at any time by retrieving its page layouts and contents from the relevant page server.

## 5    **2.7    ON-DEMAND DOCUMENTS**

When a netpage document is requested on demand, it can be personalized and delivered in much the same way as a periodical. However, since there is no shared content, delivery is made directly to the requesting printer without the use of multicast.

When a non-netpage document is requested on demand, it is not personalized, and it is delivered via a designated netpage formatting server which reformats it as a netpage document. A netpage formatting server is a special instance of a netpage publication server. The netpage formatting server has knowledge of various Internet document formats, including Adobe's Portable Document Format (PDF), and Hypertext Markup Language (HTML). In the case of HTML, it can make use of the higher resolution of the printed page to present Web pages in a multi-column format, with a table of contents. It can automatically include all Web pages directly linked to the requested page. The user can tune this behavior via a preference.

The netpage formatting server makes standard netpage behavior, including interactivity and persistence, available on any Internet document, no matter what its origin and format. It hides knowledge of different document formats from both the netpage printer and the netpage page server, and hides knowledge of the netpage system from Web servers.

## 3        **SECURITY**

### 3.1        **CRYPTOGRAPHY**

Cryptography is used to protect sensitive information, both in storage and in transit, and to authenticate parties to a transaction. There are two classes of cryptography in widespread use: secret-key cryptography and public-key cryptography. The netpage network uses both classes of cryptography.

Secret-key cryptography, also referred to as symmetric cryptography, uses the

same key to encrypt and decrypt a message. Two parties wishing to exchange messages must first arrange to securely exchange the secret key.

Public-key cryptography, also referred to as asymmetric cryptography, uses two encryption keys. The two keys are mathematically related in such a way that any message encrypted using one key can only be decrypted using the other key. One of these keys is then published, while the other is kept private. The public key is used to encrypt any message intended for the holder of the private key. Once encrypted using the public key, a message can only be decrypted using the private key. Thus two parties can securely exchange messages without first having to exchange a secret key. To ensure that the private key is secure, it is normal for the holder of the private key to generate the key pair.

Public-key cryptography can be used to create a digital signature. The holder of the private key can create a known hash of a message and then encrypt the hash using the private key. Anyone can then verify that the encrypted hash constitutes the “signature” of the holder of the private key with respect to that particular message by decrypting the encrypted hash using the public key and verifying the hash against the message. If the signature is appended to the message, then the recipient of the message can verify both that the message is genuine and that it has not been altered in transit.

To make public-key cryptography work, there has to be a way to distribute public keys which prevents impersonation. This is normally done using certificates and certificate authorities. A certificate authority is a trusted third party which authenticates the connection between a public key and someone’s identity. The certificate authority verifies the person’s identity by examining identity documents, and then creates and signs a digital certificate containing the person’s identity details and public key. Anyone who trusts the certificate authority can use the public key in the certificate with a high degree of certainty that it is genuine. They just have to verify that the certificate has indeed been signed by the certificate authority, whose public key is well-known.

In most transaction environments, public-key cryptography is only used to create digital signatures and to securely exchange secret session keys. Secret-key cryptography is used for all other purposes.

In the following discussion, when reference is made to the *secure* transmission

of information between a netpage printer and a server, what actually happens is that the printer obtains the server's certificate, authenticates it with reference to the certificate authority, uses the public key-exchange key in the certificate to exchange a secret session key with the server, and then uses the secret session key to encrypt the message data. A  
5 *session* key, by definition, can have an arbitrarily short lifetime.

### 3.2 NETPAGE PRINTER SECURITY

Each netpage printer is assigned a pair of unique identifiers at time of manufacture which are stored in read-only memory in the printer and in the netpage registration server database. The first ID 62 is public and uniquely identifies the printer  
10 on the netpage network. The second ID is secret and is used when the printer is first registered on the network.

When the printer connects to the netpage network for the first time after installation, it creates a signature public/private key pair. It transmits the secret ID and the public key securely to the netpage registration server. The server compares the secret  
15 ID against the printer's secret ID recorded in its database, and accepts the registration if the IDs match. It then creates and signs a certificate containing the printer's public ID and public signature key, and stores the certificate in the registration database.

The netpage registration server acts as a certificate authority for netpage printers, since it has access to secret information allowing it to verify printer identity.

20 When a user subscribes to a publication, a record is created in the netpage registration server database authorizing the publisher to print the publication to the user's default printer or a specified printer. Every document sent to a printer via a page server is addressed to a particular user and is signed by the publisher using the publisher's private signature key. The page server verifies, via the registration database, that the publisher is  
25 authorized to deliver the publication to the specified user. The page server verifies the signature using the publisher's public key, obtained from the publisher's certificate stored in the registration database.

The netpage registration server accepts requests to add printing authorizations to the database, so long as those requests are initiated via a pen registered to the printer.

### 3.3 NETPAGE PEN SECURITY

Each netpage pen is assigned a unique identifier at time of manufacture which is stored in read-only memory in the pen and in the netpage registration server database. The pen ID 61 uniquely identifies the pen on the netpage network.

- 5           A netpage pen can “know” a number of netpage printers, and a printer can “know” a number of pens. A pen communicates with a printer via a radio frequency signal whenever it is within range of the printer. Once a pen and printer are registered, they regularly exchange session keys. Whenever the pen transmits digital ink to the printer, the digital ink is always encrypted using the appropriate session key. Digital ink  
10 is never transmitted in the clear.

A pen stores a session key for every printer it knows, indexed by printer ID, and a printer stores a session key for every pen it knows, indexed by pen ID. Both have a large but finite storage capacity for session keys, and will forget a session key on a least-recently-used basis if necessary.

- 15           When a pen comes within range of a printer, the pen and printer discover whether they know each other. If they don’t know each other, then the printer determines whether it is supposed to know the pen. This might be, for example, because the pen belongs to a user who is registered to use the printer. If the printer is meant to know the pen but doesn’t, then it initiates the automatic pen registration procedure. If the printer  
20 isn’t meant to know the pen, then it agrees with the pen to ignore it until the pen is placed in a charging cup, at which time it initiates the registration procedure.

- In addition to its public ID, the pen contains a secret key-exchange key. The key-exchange key is also recorded in the netpage registration server database at time of manufacture. During registration, the pen transmits its pen ID to the printer, and the  
25 printer transmits the pen ID to the netpage registration server. The server generates a session key for the printer and pen to use, and securely transmits the session key to the printer. It also transmits a copy of the session key encrypted with the pen’s key-exchange key. The printer stores the session key internally, indexed by the pen ID, and transmits the encrypted session key to the pen. The pen stores the session key internally, indexed  
30 by the printer ID.

Although a fake pen can impersonate a pen in the pen registration protocol,



only a real pen can decrypt the session key transmitted by the printer.

When a previously unregistered pen is first registered, it is of limited use until it is linked to a user. A registered but “un-owned” pen is only allowed to be used to request and fill in netpage user and pen registration forms, to register a new user to which the new pen is automatically linked, or to add a new pen to an existing user.

The pen uses secret-key rather than public-key encryption because of hardware performance constraints in the pen.

### 3.4 SECURE DOCUMENTS

The netpage system supports the delivery of secure documents such as tickets and coupons. The netpage printer includes a facility to print watermarks, but will only do so on request from publishers who are suitably authorized. The publisher indicates its authority to print watermarks in its certificate, which the printer is able to authenticate.

The “watermark” printing process uses an alternative dither matrix in specified “watermark” regions of the page. Back-to-back pages contain mirror-image watermark regions which coincide when printed. The dither matrices used in odd and even pages’ watermark regions are designed to produce an interference effect when the regions are viewed together, achieved by looking *through* the printed sheet.

The effect is similar to a watermark in that it is not visible when looking at only one side of the page, and is lost when the page is copied by normal means.

Pages of secure documents cannot be copied using the built-in netpage copy mechanism described in Section 1.9 above. This extends to copying netpages on netpage-aware photocopiers.

Secure documents are typically generated as part of e-commerce transactions. They can therefore include the user’s photograph which was captured when the user registered biometric information with the netpage registration server, as described in Section 2.

When presented with a secure netpage document, the recipient can verify its authenticity by requesting its status in the usual way. The unique ID of a secure document is only valid for the lifetime of the document, and secure document IDs are allocated non-contiguously to prevent their prediction by opportunistic forgers. A secure

document verification pen can be developed with built-in feedback on verification failure, to support easy point-of-presentation document verification.

Clearly neither the watermark nor the user's photograph are secure in a cryptographic sense. They simply provide a significant obstacle to casual forgery. Online document verification, particularly using a verification pen, provides an added level of security where it is needed, but is still not entirely immune to forgeries.

### **3.5 NON-REPUDIATION**

In the netpage system, forms submitted by users are delivered reliably to forms handlers and are persistently archived on netpage page servers. It is therefore impossible for recipients to repudiate delivery.

E-commerce payments made through the system, as described in Section 4, are also impossible for the payee to repudiate.

## **4 ELECTRONIC COMMERCE MODEL**

### **4.1 SECURE ELECTRONIC TRANSACTION (SET)**

The netpage system uses the Secure Electronic Transaction (SET) system as one of its payment systems. SET, having been developed by MasterCard and Visa, is organized around payment cards, and this is reflected in the terminology. However, much of the system is independent of the type of accounts being used.

In SET, cardholders and merchants register with a certificate authority and are issued with certificates containing their public signature keys. The certificate authority verifies a cardholder's registration details with the card issuer as appropriate, and verifies a merchant's registration details with the acquirer as appropriate. Cardholders and merchants store their respective private signature keys securely on their computers. During the payment process, these certificates are used to mutually authenticate a merchant and cardholder, and to authenticate them both to the payment gateway.

SET has not yet been adopted widely, partly because cardholder maintenance of keys and certificates is considered burdensome. Interim solutions which maintain cardholder keys and certificates on a server and give the cardholder access via a password have met with some success.

## 4.2 SET PAYMENTS

In the netpage system the netpage registration server acts as a proxy for the netpage user (i.e. the cardholder) in SET payment transactions.

The netpage system uses biometrics to authenticate the user and authorize SET payments. Because the system is pen-based, the biometric used is the user's on-line signature, consisting of time-varying pen position and pressure. A fingerprint biometric can also be used by designing a fingerprint sensor into the pen, although at a higher cost. The type of biometric used only affects the capture of the biometric, not the authorization aspects of the system.

The first step to being able to make SET payments is to register the user's biometric with the netpage registration server. This is done in a controlled environment, for example a bank, where the biometric can be captured at the same time as the user's identity is verified. The biometric is captured and stored in the registration database, linked to the user's record. The user's photograph is also optionally captured and linked to the record. The SET cardholder registration process is completed, and the resulting private signature key and certificate are stored in the database. The user's payment card information is also stored, giving the netpage registration server enough information to act as the user's proxy in any SET payment transaction.

When the user eventually supplies the biometric to complete a payment, for example by signing a netpage order form, the printer securely transmits the order information, the pen ID and the biometric data to the netpage registration server. The server verifies the biometric with respect to the user identified by the pen ID, and from then on acts as the user's proxy in completing the SET payment transaction.

## 4.3 MICRO-PAYMENTS

The netpage system includes a mechanism for micro-payments, to allow the user to be conveniently charged for printing low-cost documents on demand and for copying copyright documents, and possibly also to allow the user to be reimbursed for expenses incurred in printing advertising material. The latter depends on the level of subsidy already provided to the user.

When the user registers for e-commerce, a network account is established which aggregates micro-payments. The user receives a statement on a regular basis, and

can settle any outstanding debit balance using the standard payment mechanism.

The network account can be extended to aggregate subscription fees for periodicals, which would also otherwise be presented to the user in the form of individual statements.

#### 5 4.4 TRANSACTIONS

When a user requests a netpage in a particular application context, the application is able to embed a user-specific transaction ID 55 in the page. Subsequent input through the page is tagged with the transaction ID, and the application is thereby able to establish an appropriate context for the user's input.

10 When input occurs through a page which is not user-specific, however, the application must use the user's unique identity to establish a context. A typical example involves adding items from a pre-printed catalog page to the user's virtual "shopping cart". To protect the user's privacy, however, the unique user ID 60 known to the netpage system is not divulged to applications. This is to prevent different application  
15 providers from easily correlating independently accumulated behavioral data.

The netpage registration server instead maintains an anonymous relationship between a user and an application via a unique alias ID 65, as shown in Figure 24. Whenever the user activates a hyperlink tagged with the "registered" attribute, the netpage page server asks the netpage registration server to translate the associated  
20 application ID 64, together with the pen ID 61, into an alias ID 65. The alias ID is then submitted to the hyperlink's application.

The application maintains state information indexed by alias ID, and is able to retrieve user-specific state information without knowledge of the global identity of the user.

25 The system also maintains an independent certificate and private signature key for each of a user's applications, to allow it to sign application transactions on behalf of the user using only application-specific information.

To assist the system in routing product bar code (UPC) "hyperlink" activations, the system records a favorite application on behalf of the user for any number of product  
30 types.

Each application is associated with an application provider, and the system maintains an account on behalf of each application provider, to allow it to credit and debit the provider for click-through fees etc.

An application provider can be a publisher of periodical subscribed content.

- 5 The system records the user's willingness to receive the subscribed publication, as well as the expected frequency of publication.

#### 4.5 RESOURCE DESCRIPTIONS AND COPYRIGHT

A preferred embodiment of a resource description class diagram is shown in Figure 40.

- 10 Each document and content object may be described by one or more resource descriptions 842. Resource descriptions use the Dublin Core metadata element set, which is designed to facilitate discovery of electronic resources. Dublin Core metadata conforms to the World Wide Web Consortium (W3C) Resource Description Framework (RDF).
- 15 A resource description may identify rights holders 920. The netpage system automatically transfers copyright fees from users to rights holders when users print copyright content.

#### 5 COMMUNICATIONS PROTOCOLS

- 20 A communications protocol defines an ordered exchange of messages between entities. In the netpage system, entities such as pens, printers and servers utilise a set of defined protocols to cooperatively handle user interaction with the netpage system.

- 25 Each protocol is illustrated by way of a sequence diagram in which the horizontal dimension is used to represent message flow and the vertical dimension is used to represent time. Each entity is represented by a rectangle containing the name of the entity and a vertical column representing the lifeline of the entity. During the time an entity exists, the lifeline is shown as a dashed line. During the time an entity is active, the lifeline is shown as a double line. Because the protocols considered here do not create or destroy entities, lifelines are generally cut short as soon as an entity ceases to participate in a protocol.

## 5.1 SUBSCRIPTION DELIVERY PROTOCOL

A preferred embodiment of a subscription delivery protocol is shown in Figure 43.

5 A large number of users may subscribe to a periodical publication. Each user's edition may be laid out differently, but many users' editions will share common content such as text objects and image objects. The subscription delivery protocol therefore delivers document structures to individual printers via pointcast, but delivers shared content objects via multicast.

10 The application (i.e. publisher) first obtains a document ID 51 for each document from an ID server 12. It then sends each document structure, including its document ID and page descriptions, to the page server 10 responsible for the document's newly allocated ID. It includes its own application ID 64, the subscriber's alias ID 65, and the relevant set of multicast channel names. It signs the message using its private signature key.

15 The page server uses the application ID and alias ID to obtain from the registration server the corresponding user ID 60, the user's selected printer ID 62 (which may be explicitly selected for the application, or may be the user's default printer), and the application's certificate.

20 The application's certificate allows the page server to verify the message signature. The page server's request to the registration server fails if the application ID and alias ID don't together identify a subscription 808.

The page server then allocates document and page instance IDs and forwards the page descriptions, including page IDs 50, to the printer. It includes the relevant set of multicast channel names for the printer to listen to.

25 It then returns the newly allocated page IDs to the application for future reference.

30 Once the application has distributed all of the document structures to the subscribers' selected printers via the relevant page servers, it multicasts the various subsets of the shared objects on the previously selected multicast channels. Both page servers and printers monitor the appropriate multicast channels and receive their required

content objects. They are then able to populate the previously pointcast document structures. This allows the page servers to add complete documents to their databases, and it allows the printers to print the documents.

## 5.2 HYPERLINK ACTIVATION PROTOCOL

5 A preferred embodiment of a hyperlink activation protocol is shown in Figure 45.

When a user clicks on a netpage with a netpage pen, the pen communicates the click to the nearest netpage printer 601. The click identifies the page and a location on the page. The printer already knows the ID 61 of the pen from the pen connection  
10 protocol.

The printer determines, via the DNS, the network address of the page server 10a handling the particular page ID 50. The address may already be in its cache if the user has recently interacted with the same page. The printer then forwards the pen ID, its own printer ID 62, the page ID and click location to the page server.

15 The page server loads the page description 5 identified by the page ID and determines which input element's zone 58, if any, the click lies in. Assuming the relevant input element is a hyperlink element 844, the page server then obtains the associated application ID 64 and link ID 54, and determines, via the DNS, the network address of the application server hosting the application 71.

20 The page server uses the pen ID 61 to obtain the corresponding user ID 60 from the registration server 11, and then allocates a globally unique hyperlink request ID 52 and builds a hyperlink request 934. The hyperlink request class diagram is shown in Figure 44. The hyperlink request records the IDs of the requesting user and printer, and identifies the clicked hyperlink instance 862. The page server then sends its own server  
25 ID 53, the hyperlink request ID, and the link ID to the application.

The application produces a response document according to application-specific logic, and obtains a document ID 51 from an ID server 12. It then sends the document to the page server 10b responsible for the document's newly allocated ID, together with the requesting page server's ID and the hyperlink request ID.

30 The second page server sends the hyperlink request ID and application ID to

the first page server to obtain the corresponding user ID and printer ID 62. The first page server rejects the request if the hyperlink request has expired or is for a different application.

5 The second page server allocates document instance and page IDs 50, returns the newly allocated page IDs to the application, adds the complete document to its own database, and finally sends the page descriptions to the requesting printer.

10 The hyperlink instance may include a meaningful transaction ID 55, in which case the first page server includes the transaction ID in the message sent to the application. This allows the application to establish a transaction-specific context for the hyperlink activation.

15 If the hyperlink requires a user alias, i.e. its “alias required” attribute is set, then the first page server sends both the pen ID 61 and the hyperlink’s application ID 64 to the registration server 11 to obtain not just the user ID corresponding to the pen ID but also the alias ID 65 corresponding to the application ID and the user ID. It includes the alias ID in the message sent to the application, allowing the application to establish a user-specific context for the hyperlink activation.

### 5.3 HANDWRITING RECOGNITION PROTOCOL

20 When a user draws a stroke on a netpage with a netpage pen, the pen communicates the stroke to the nearest netpage printer. The stroke identifies the page and a path on the page.

The printer forwards the pen ID 61, its own printer ID 62, the page ID 50 and stroke path to the page server 10 in the usual way.

25 The page server loads the page description 5 identified by the page ID and determines which input element’s zone 58, if any, the stroke intersects. Assuming the relevant input element is a text field 878, the page server appends the stroke to the text field’s digital ink.

30 After a period of inactivity in the zone of the text field, the page server sends the pen ID and the pending strokes to the registration server 11 for interpretation. The registration server identifies the user corresponding to the pen, and uses the user’s accumulated handwriting model 822 to interpret the strokes as handwritten text. Once it



has converted the strokes to text, the registration server returns the text to the requesting page server. The page server appends the text to the text value of the text field.

#### **5.4 SIGNATURE VERIFICATION PROTOCOL**

Assuming the input element whose zone the stroke intersects is a signature  
5 field 880, the page server 10 appends the stroke to the signature field's digital ink.

After a period of inactivity in the zone of the signature field, the page server  
sends the pen ID 61 and the pending strokes to the registration server 11 for verification.  
It also sends the application ID 64 associated with the form of which the signature field  
is part, as well as the form ID 56 and the current data content of the form. The  
10 registration server identifies the user corresponding to the pen, and uses the user's  
dynamic signature biometric 818 to verify the strokes as the user's signature. Once it has  
verified the signature, the registration server uses the application ID 64 and user ID 60 to  
identify the user's application-specific private signature key. It then uses the key to  
generate a digital signature of the form data, and returns the digital signature to the  
15 requesting page server. The page server assigns the digital signature to the signature field  
and sets the associated form's status to frozen.

The digital signature includes the alias ID 65 of the corresponding user. This  
allows a single form to capture multiple users' signatures.

#### **5.5 FORM SUBMISSION PROTOCOL**

20 A preferred embodiment of a form submission protocol is shown in Figure 46.

Form submission occurs via a form hyperlink activation. It thus follows the  
protocol defined in Section 5.2, with some form-specific additions.

In the case of a form hyperlink, the hyperlink activation message sent by the  
page server 10 to the application 71 also contains the form ID 56 and the current data  
25 content of the form. If the form contains any signature fields, then the application  
verifies each one by extracting the alias ID 65 associated with the corresponding digital  
signature and obtaining the corresponding certificate from the registration server 11.

#### **5.6 COMMISSION PAYMENT PROTOCOL**

A preferred embodiment of a commission payment protocol is shown in Figure

47.

In an e-commerce environment, fees and commissions may be payable from an application provider to a publisher on click-throughs, transactions and sales. Commissions on fees and commissions on commissions may also be payable from the publisher to the provider of the printer.

The hyperlink request ID 52 is used to route a fee or commission credit from the target application provider 70a (e.g. merchant) to the source application provider 70b (i.e. publisher), and from the source application provider 70b to the printer provider 72.

The target application receives the hyperlink request ID from the page server 10 when the hyperlink is first activated, as described in Section 5.2. When the target application needs to credit the source application provider, it sends the application provider credit to the original page server together with the hyperlink request ID. The page server uses the hyperlink request ID to identify the source application, and sends the credit on to the relevant registration server 11 together with the source application ID 64, its own server ID 53, and the hyperlink request ID. The registration server credits the corresponding application provider's account 827. It also notifies the application provider.

If the application provider needs to credit the printer provider, it sends the printer provider credit to the original page server together with the hyperlink request ID. The page server uses the hyperlink request ID to identify the printer, and sends the credit on to the relevant registration server together with the printer ID. The registration server credits the corresponding printer provider account 814.

The source application provider is optionally notified of the identity of the target application provider, and the printer provider of the identity of the source application provider.

## **6. NETPAGE PEN DESCRIPTION**

### **6.1 PEN MECHANICS**

Referring to Figures 8 and 9, the pen, generally designated by reference numeral 101, includes a housing 102 in the form of a plastics moulding having walls 103 defining an interior space 104 for mounting the pen components. The pen top 105 is in

operation rotatably mounted at one end 106 of the housing 102. A semi-transparent cover 107 is secured to the opposite end 108 of the housing 102. The cover 107 is also of moulded plastics, and is formed from semi-transparent material in order to enable the user to view the status of the LED mounted within the housing 102. The cover 107  
5 includes a main part 109 which substantially surrounds the end 108 of the housing 102 and a projecting portion 110 which projects back from the main part 109 and fits within a corresponding slot 111 formed in the walls 103 of the housing 102. A radio antenna 112 is mounted behind the projecting portion 110, within the housing 102. Screw threads 113 surrounding an aperture 113A on the cover 107 are arranged to receive a metal end  
10 piece 114, including corresponding screw threads 115. The metal end piece 114 is removable to enable ink cartridge replacement.

Also mounted within the cover 107 is a tri-color status LED 116 on a flex PCB 117. The antenna 112 is also mounted on the flex PCB 117. The status LED 116 is mounted at the top of the pen 101 for good all-around visibility.

15 The pen can operate both as a normal marking ink pen and as a non-marking stylus. An ink pen cartridge 118 with nib 119 and a stylus 120 with stylus nib 121 are mounted side by side within the housing 102. Either the ink cartridge nib 119 or the stylus nib 121 can be brought forward through open end 122 of the metal end piece 114, by rotation of the pen top 105. Respective slider blocks 123 and 124 are mounted to the  
20 ink cartridge 118 and stylus 120, respectively. A rotatable cam barrel 125 is secured to the pen top 105 in operation and arranged to rotate therewith. The cam barrel 125 includes a cam 126 in the form of a slot within the walls 181 of the cam barrel. Cam followers 127 and 128 projecting from slider blocks 123 and 124 fit within the cam slot 126. On rotation of the cam barrel 125, the slider blocks 123 or 124 move relative to  
25 each other to project either the pen nib 119 or stylus nib 121 out through the hole 122 in the metal end piece 114. The pen 101 has three states of operation. By turning the top 105 through 90° steps, the three states are:

- Stylus 120 nib 121 out;
- Ink cartridge 118 nib 119 out; and
- 30 • Neither ink cartridge 118 nib 119 out nor stylus 120 nib 121 out.

A second flex PCB 129, is mounted on an electronics chassis 130 which sits within the housing 102. The second flex PCB 129 mounts an infrared LED 131 for providing infrared radiation for projection onto the surface. An image sensor 132 is provided mounted on the second flex PCB 129 for receiving reflected radiation from the surface. The second flex PCB 129 also mounts a radio frequency chip 133, which includes an RF transmitter and RF receiver, and a controller chip 134 for controlling operation of the pen 101. An optics block 135 (formed from moulded clear plastics) sits within the cover 107 and projects an infrared beam onto the surface and receives images onto the image sensor 132. Power supply wires 136 connect the components on the second flex PCB 129 to battery contacts 137 which are mounted within the cam barrel 125. A terminal 138 connects to the battery contacts 137 and the cam barrel 125. A three volt rechargeable battery 139 sits within the cam barrel 125 in contact with the battery contacts. An induction charging coil 140 is mounted about the second flex PCB 129 to enable recharging of the battery 139 via induction. The second flex PCB 129 also mounts an infrared LED 143 and infrared photodiode 144 for detecting displacement in the cam barrel 125 when either the stylus 120 or the ink cartridge 118 is used for writing, in order to enable a determination of the force being applied to the surface by the pen nib 119 or stylus nib 121. The IR photodiode 144 detects light from the IR LED 143 via reflectors (not shown) mounted on the slider blocks 123 and 124.

Rubber grip pads 141 and 142 are provided towards the end 108 of the housing 102 to assist gripping the pen 101, and top 105 also includes a clip 142 for clipping the pen 101 to a pocket.

## 6.2 PEN CONTROLLER

The pen 101 is arranged to determine the position of its nib (stylus nib 121 or ink cartridge nib 119) by imaging, in the infrared spectrum, an area of the surface in the vicinity of the nib. It records the location data from the nearest location tag, and is arranged to calculate the distance of the nib 121 or 119 from the location tag utilising optics 135 and controller chip 134. The controller chip 134 calculates the orientation of the pen and the nib-to-tag distance from the perspective distortion observed on the imaged tag.

Utilising the RF chip 133 and antenna 112 the pen 101 can transmit the digital

ink data (which is encrypted for security and packaged for efficient transmission) to the computing system.

When the pen is in range of a receiver, the digital ink data is transmitted as it is formed. When the pen 101 moves out of range, digital ink data is buffered within the pen 101 (the pen 101 circuitry includes a buffer arranged to store digital ink data for approximately 12 minutes of the pen motion on the surface) and can be transmitted later.

The controller chip 134 is mounted on the second flex PCB 129 in the pen 101. Figure 10 is a block diagram illustrating in more detail the architecture of the controller chip 134. Figure 10 also shows representations of the RF chip 133, the image sensor 132, the tri-color status LED 116, the IR illumination LED 131, the IR force sensor LED 143, and the force sensor photodiode 144.

The pen controller chip 134 includes a controlling processor 145. Bus 146 enables the exchange of data between components of the controller chip 134. Flash memory 147 and a 512 KB DRAM 148 are also included. An analog-to-digital converter 149 is arranged to convert the analog signal from the force sensor photodiode 144 to a digital signal.

An image sensor interface 152 interfaces with the image sensor 132. A transceiver controller 153 and base band circuit 154 are also included to interface with the RF chip 133 which includes an RF circuit 155 and RF resonators and inductors 156 connected to the antenna 112.

The controlling processor 145 captures and decodes location data from tags from the surface via the image sensor 132, monitors the force sensor photodiode 144, controls the LEDs 116, 131 and 143, and handles short-range radio communication via the radio transceiver 153. It is a medium-performance (~40MHz) general-purpose RISC processor.

The processor 145, digital transceiver components (transceiver controller 153 and baseband circuit 154), image sensor interface 152, flash memory 147 and 512KB DRAM 148 are integrated in a single controller ASIC. Analog RF components (RF circuit 155 and RF resonators and inductors 156) are provided in the separate RF chip.

The image sensor is a 215x215 pixel CCD (such a sensor is produced by

Matsushita Electronic Corporation, and is described in a paper by Itakura, K T Nobusada, N Okusenya, R Nagayoshi, and M Ozaki, "A 1mm 50k-Pixel IT CCD Image Sensor for Miniature Camera System", IEEE Transactions on Electronic Devices, Volt 47, number 1, January 2000, which is incorporated herein by reference) with an IR filter.

5           The controller ASIC 134 enters a quiescent state after a period of inactivity when the pen 101 is not in contact with a surface. It incorporates a dedicated circuit 150 which monitors the force sensor photodiode 144 and wakes up the controller 134 via the power manager 151 on a pen-down event.

10           The radio transceiver communicates in the unlicensed 900MHz band normally used by cordless telephones, or alternatively in the unlicensed 2.4GHz industrial, scientific and medical (ISM) band, and uses frequency hopping and collision detection to provide interference-free communication.

15           In an alternative embodiment, the pen incorporates an Infrared Data Association (IrDA) interface for short-range communication with a base station or netpage printer.

          In a further embodiment, the pen 101 includes a pair of orthogonal accelerometers mounted in the normal plane of the pen 101 axis. The accelerometers 190 are shown in Figures 9 and 10 in ghost outline.

20           The provision of the accelerometers enables this embodiment of the pen 101 to sense motion without reference to surface location tags, allowing the location tags to be sampled at a lower rate. Each location tag ID can then identify an object of interest rather than a position on the surface. For example, if the object is a user interface input element (e.g. a command button), then the tag ID of each location tag within the area of the input element can directly identify the input element.

25           The acceleration measured by the accelerometers in each of the x and y directions is integrated with respect to time to produce an instantaneous velocity and position.

30           Since the starting position of the stroke is not known, only relative positions within a stroke are calculated. Although position integration accumulates errors in the sensed acceleration, accelerometers typically have high resolution, and the time duration

of a stroke, over which errors accumulate, is short.

## **7. NETPAGE PRINTER DESCRIPTION**

### **7.1 PRINTER MECHANICS**

The vertically-mounted netpage wallprinter 601 is shown fully assembled in  
5 Figure 11. It prints netpages on Letter/A4 sized media using duplexed 8½" Memjet™  
print engines 602 and 603, as shown in Figures 12 and 12a. It uses a straight paper path  
with the paper 604 passing through the duplexed print engines 602 and 603 which print  
both sides of a sheet simultaneously, in full color and with full bleed.

An integral binding assembly 605 applies a strip of glue along one edge of each  
10 printed sheet, allowing it to adhere to the previous sheet when pressed against it. This  
creates a final bound document 618 which can range in thickness from one sheet to  
several hundred sheets.

The replaceable ink cartridge 627, shown in Figure 13 coupled with the  
duplexed print engines, has bladders or chambers for storing fixative, adhesive, and  
15 cyan, magenta, yellow, black and infrared inks. The cartridge also contains a micro air  
filter in a base molding. The micro air filter interfaces with an air pump 638 inside the  
printer via a hose 639. This provides filtered air to the printheads to prevent ingress of  
micro particles into the Memjet™ printheads 350 which might otherwise clog the  
printhead nozzles. By incorporating the air filter within the cartridge, the operational life  
20 of the filter is effectively linked to the life of the cartridge. The ink cartridge is a fully  
recyclable product with a capacity for printing and gluing 3000 pages (1500 sheets).

Referring to Figure 12, the motorized media pick-up roller assembly 626  
pushes the top sheet directly from the media tray past a paper sensor on the first print  
engine 602 into the duplexed Memjet™ printhead assembly. The two Memjet™ print  
25 engines 602 and 603 are mounted in an opposing in-line sequential configuration along  
the straight paper path. The paper 604 is drawn into the first print engine 602 by integral,  
powered pick-up rollers 626. The position and size of the paper 604 is sensed and full  
bleed printing commences. Fixative is printed simultaneously to aid drying in the  
shortest possible time.

30 The paper exits the first Memjet™ print engine 602 through a set of powered

exit spike wheels (aligned along the straight paper path), which act against a rubberized roller. These spike wheels contact the 'wet' printed surface and continue to feed the sheet 604 into the second Memjet™ print engine 603.

Referring to Figures 12 and 12a, the paper 604 passes from the duplexed print engines 602 and 603 into the binder assembly 605. The printed page passes between a  
5 powered spike wheel axle 670 with a fibrous support roller and another movable axle with spike wheels and a momentary action glue wheel. The movable axle/glue assembly 673 is mounted to a metal support bracket and it is transported forward to interface with the powered axle 670 via gears by action of a camshaft. A separate motor powers this  
10 camshaft.

The glue wheel assembly 673 consists of a partially hollow axle 679 with a rotating coupling for the glue supply hose 641 from the ink cartridge 627. This axle 679 connects to a glue wheel, which absorbs adhesive by capillary action through radial holes. A molded housing 682 surrounds the glue wheel, with an opening at the front.  
15 Pivoting side moldings and sprung outer doors are attached to the metal bracket and hinge out sideways when the rest of the assembly 673 is thrust forward. This action exposes the glue wheel through the front of the molded housing 682. Tension springs close the assembly and effectively cap the glue wheel during periods of inactivity.

As the sheet 604 passes into the glue wheel assembly 673, adhesive is applied  
20 to one vertical edge on the front side (apart from the first sheet of a document) as it is transported down into the binding assembly 605.

## 7.2 PRINTER CONTROLLER ARCHITECTURE

The netpage printer controller consists of a controlling processor 750, a factory-installed or field-installed network interface module 625, a radio transceiver (transceiver  
25 controller 753, baseband circuit 754, RF circuit 755, and RF resonators and inductors 756), dual raster image processor (RIP) DSPs 757, duplexed print engine controllers 760a and 760b, flash memory 658, and 64MB of DRAM 657, as illustrated in Figure 14.

The controlling processor handles communication with the network 19 and with local wireless netpage pens 101, senses the help button 617, controls the user  
30 interface LEDs 613-616, and feeds and synchronizes the RIP DSPs 757 and print engine



controllers 760. It consists of a medium-performance general-purpose microprocessor. The controlling processor 750 communicates with the print engine controllers 760 via a high-speed serial bus 659.

5       The RIP DSPs rasterize and compress page descriptions to the netpage printer's compressed page format. Each print engine controller expands, dithers and prints page images to its associated Memjet™ printhead 350 in real time (i.e. at over 30 pages per minute). The duplexed print engine controllers print both sides of a sheet simultaneously.

10       The master print engine controller 760a controls the paper transport and monitors ink usage in conjunction with the master QA chip 665 and the ink cartridge QA chip 761.

      The printer controller's flash memory 658 holds the software for both the processor 750 and the DSPs 757, as well as configuration data. This is copied to main memory 657 at boot time.

15       The processor 750, DSPs 757, and digital transceiver components (transceiver controller 753 and baseband circuit 754) are integrated in a single controller ASIC 656. Analog RF components (RF circuit 755 and RF resonators and inductors 756) are provided in a separate RF chip 762. The network interface module 625 is separate, since netpage printers allow the network connection to be factory-selected or field-selected. Flash memory 658 and the 2×256Mbit (64MB) DRAM 657 is also off-chip. The print  
20       engine controllers 760 are provided in separate ASICs.

      A variety of network interface modules 625 are provided, each providing a netpage network interface 751 and optionally a local computer or network interface 752. Netpage network Internet interfaces include POTS modems, Hybrid Fiber-Coax (HFC) cable modems, ISDN modems, DSL modems, satellite transceivers, current and next-  
25       generation cellular telephone transceivers, and wireless local loop (WLL) transceivers. Local interfaces include IEEE 1284 (parallel port), 10Base-T and 100Base-T Ethernet, USB and USB 2.0, IEEE 1394 (Firewire), and various emerging home networking interfaces. If an Internet connection is available on the local network, then the local network interface can be used as the netpage network interface.

30       The radio transceiver 753 communicates in the unlicensed 900MHz band

normally used by cordless telephones, or alternatively in the unlicensed 2.4GHz industrial, scientific and medical (ISM) band, and uses frequency hopping and collision detection to provide interference-free communication.

5 The printer controller optionally incorporates an Infrared Data Association (IrDA) interface for receiving data “squirted” from devices such as netpage cameras. In an alternative embodiment, the printer uses the IrDA interface for short-range communication with suitably configured netpage pens.

### 7.2.1 RASTERIZATION AND PRINTING

10 Once the main processor 750 has received and verified the document’s page layouts and page objects, it runs the appropriate RIP software on the DSPs 757.

The DSPs 757 rasterize each page description and compress the rasterized page image. The main processor stores each compressed page image in memory. The simplest way to load-balance multiple DSPs is to let each DSP rasterize a separate page. The DSPs can always be kept busy since an arbitrary number of rasterized pages can, in  
15 general, be stored in memory. This strategy only leads to potentially poor DSP utilization when rasterizing short documents.

Watermark regions in the page description are rasterized to a contone-resolution bi-level bitmap which is losslessly compressed to negligible size and which forms part of the compressed page image.

20 The infrared (IR) layer of the printed page contains coded netpage tags at a density of about six per inch. Each tag encodes the page ID, tag ID, and control bits, and the data content of each tag is generated during rasterization and stored in the compressed page image.

The main processor 750 passes back-to-back page images to the duplexed print  
25 engine controllers 760. Each print engine controller 760 stores the compressed page image in its local memory, and starts the page expansion and printing pipeline. Page expansion and printing is pipelined because it is impractical to store an entire 114MB bi-level CMYK+IR page image in memory.

## 7.2.2 PRINT ENGINE CONTROLLER

The page expansion and printing pipeline of the print engine controller 760 consists of a high speed IEEE 1394 serial interface 659, a standard JPEG decoder 763, a standard Group 4 Fax decoder 764, a custom halftoner/compositor unit 765, a custom tag encoder 766, a line loader/formatter unit 767, and a custom interface 768 to the Memjet™ printhead 350.

The print engine controller 360 operates in a double buffered manner. While one page is loaded into DRAM 769 via the high speed serial interface 659, the previously loaded page is read from DRAM 769 and passed through the print engine controller pipeline. Once the page has finished printing, the page just loaded is printed while another page is loaded.

The first stage of the pipeline expands (at 763) the JPEG-compressed contone CMYK layer, expands (at 764) the Group 4 Fax-compressed bi-level black layer, and renders (at 766) the bi-level netpage tag layer according to the tag format defined in section 1.2, all in parallel. The second stage dithers (at 765) the contone CMYK layer and composites (at 765) the bi-level black layer over the resulting bi-level CMYK layer. The resultant bi-level CMYK+IR dot data is buffered and formatted (at 767) for printing on the Memjet™ printhead 350 via a set of line buffers. Most of these line buffers are stored in the off-chip DRAM. The final stage prints the six channels of bi-level dot data (including fixative) to the Memjet™ printhead 350 via the printhead interface 768.

When several print engine controllers 760 are used in unison, such as in a duplexed configuration, they are synchronized via a shared line sync signal 770. Only one print engine 760, selected via the external master/slave pin 771, generates the line sync signal 770 onto the shared line.

The print engine controller 760 contains a low-speed processor 772 for synchronizing the page expansion and rendering pipeline, configuring the printhead 350 via a low-speed serial bus 773, and controlling the stepper motors 675, 676.

In the 8½" versions of the netpage printer, the two print engines each prints 30 Letter pages per minute along the long dimension of the page (11"), giving a line rate of 8.8 kHz at 1600 dpi. In the 12" versions of the netpage printer, the two print engines each prints 45 Letter pages per minute along the short dimension of the page (8½"),

giving a line rate of 10.2 kHz. These line rates are well within the operating frequency of the Memjet™ printhead, which in the current design exceeds 30 kHz.

## 8 NETPAGE TAGS

### 8.1 TAG TILING

#### 5 8.1.1 Planar Surface Tag Tiling

In order to support “single-click” interaction with a tagged region via a sensing device, the sensing device must be able to see at least one entire tag 4 in its field of view no matter where in the region or at what orientation it is positioned. The required diameter of the field of view of the sensing device is therefore a function of the size and  
10 spacing of the tags 4.

In the case where the tag shape is circular, such as the preferred tag 4 described earlier, the minimum diameter  $m$  of the sensor field of view is obtained when the tags 500, of diameter  $k$ , are tiled on an equilateral triangular grid, as shown in Figure 52 and defined in EQ 1. This is achieved when the center-to-center tag spacing is the same as  
15 the tag diameter  $k$ .

With a tag diameter  $k$  of 256 dots (~4 mm at 1600 dpi),  $m$  is therefore 552 dots (~8.8 mm). With a quiet area of 16 dots, i.e. an effective tag diameter  $k$  of 272 dots (~4.3 mm),  $m$  increases to 587 dots (~9.3 mm).

When the tags 4 are moved a distance  $s$  apart, where  $s$  is at least as large as  $k$ ,  
20 then the minimum field of view is given by EQ 2.

When no overlap is desired in the horizontal direction between successive lines of tags 500, for example to make tag rendering easier, the tags must be moved apart by a minimum amount given by EQ 3. For a 256-dot diameter tag,  $u$  is therefore 40 dots (~0.6 mm at 1600 dpi). Since this exceeds the quiet area required for the tag, the quiet  
25 area can be ignored if tag lines are rendered to not overlap.

Setting  $s = k + u$  in EQ 2 gives EQ 4. For a 256-dot diameter tag,  $s$  is therefore 296 dots (~4.7 mm at 1600 dpi), and  $m$  is 598 dots (~9.5 mm).

#### 8.1.2 Spherical Surface Tag Tiling

A regular icosahedron is often used as the basis for generating an almost

regular triangular tiling of a sphere. A regular icosahedron, such as icosahedron 526 in Figure 53, is composed of twenty equal-sized equilateral triangular faces 528 sharing thirty edges 530 and twelve vertices 532, with five of the edges 530 meeting at each of the vertices 532.

5           To achieve the required tiling, the icosahedron 526 is inscribed in a target sphere, and each triangle 528 of the icosahedron 526 is subdivided into an equal number of equal-sized equilateral subdivision triangles to yield the desired total number of triangles. If each edge 530 of the icosahedron is divided into  $v$  equal intervals, defining a set of  $v-1$  points along each edge, and each pair of corresponding points along any two  
10 adjacent edges is joined by a line parallel to the other shared adjacent edge, the lines so drawn intersect at the vertices of the desired equal-sized and equilateral subdivision triangles, resulting in the creation of  $v^2$  triangles per triangular face 528 of the icosahedron 526, or  $20v^2$  triangles in all. Of the resulting  $10v^2 + 2$  vertices, five triangular faces meet at each of the twelve original vertices of the icosahedron 526, and  
15 six triangular faces meet at each of the remaining vertices. The twelve original vertices 532 already lie on the sphere, while the remaining vertices lie inside the sphere. Each created vertex is therefore centrally projected onto the sphere, giving the desired tiling.

A sphere approximated by a regular polyhedron in this way is referred to as a  
20 geodesic, and the parameter  $v$  is referred to as the frequency of the geodesic. Figure 54 shows an icosahedral geodesic 534 with  $v=3$ , i.e. with 180 faces 528.

The closer a subdivision triangle is to the center of a face of the icosahedron 526, the further it is from the surface of the sphere, and hence the larger it is when projected onto the sphere. To minimise variation in the size of projected subdivision  
25 triangles, subdivision vertices can systematically be displaced prior to projection (Tegmark, M., "An Icosahedron-Based Method for Pixelizing the Celestial Sphere", ApJ Letters, 470, L81, October 14, 1996). If  $v = 1$  then no vertices are created and the angle subtended by a triangular face at a vertex remains  $60^\circ$ . As  $v$  increases, however, the surface defined by the five triangular faces surrounding each original vertex becomes  
30 increasingly flat, and the vertex angle of each triangular face converges on  $72^\circ$  (i.e.  $360^\circ / 5$ ). This defines the worst case for a tag tiling of a sphere. In a  $72^\circ$  isosceles triangle the

base length is 1.18 times the length of the two sides. The maximum tag spacing  $s$  for the purposes of calculating the sensor field of view is therefore close to  $1.18k$ . With a tag diameter of 256 dots and a quiet area of 16 dots, i.e. an effective tag diameter  $k$  of 272 dots ( $\sim 4.3$  mm),  $m$  is therefore 643 dots ( $\sim 10.2$  mm) according to EQ 2.

- 5           The angle subtended by each edge of an icosahedron at the center of the circumscribing sphere is given by EQ 5

For a sphere of radius  $r$  the arc length of each centrally projected edge is  $r\theta$ . Given a tag diameter of  $K$  in the same units as  $r$ , the number of tags  $n$  required to cover the sphere is given by EQ 6.

- 10           For a given  $n$ ,  $r$  is limited by EQ 7.

If  $n$  is limited to  $2^{16}$ , to allow the use of a 16-bit tag ID without requiring multiple regions to cover the sphere, and  $K$  is taken to be 4.3 mm as above, then  $r$  is limited to  $\sim 310$  mm.

- 15           A typical globe has a radius of 160 mm. Its projected arc length of  $\sim 177$  mm fits 41 evenly spaced tags with negligible additional spacing. Such a globe uses 16812 tags in total.

### 8.1.3 Arbitrary Curved Surface Tag Tiling

- A triangle mesh can approximate a surface of arbitrary topography and topology without introducing discontinuities or singularities, with the local scale of the mesh being dictated by the local curvature of the surface and an error bound. Assuming the existence of a triangle mesh for a particular surface, an effective non-regular tiling of tags can be produced as long as each mesh triangle respects a minimum vertex angle and a minimum edge length. A tiling is considered effective with respect to a particular sensing device if the field of view of the sensing device is guaranteed to include at least one complete tag at any position of the sensing device on the surface.
- 20
- 25

- The tiling procedure starts by placing a tag at each vertex of the mesh, so the minimum edge length is the same as the tag diameter  $k$ . The tiling procedure proceeds by inserting a tag at the midpoint of any edge whose length exceeds a maximum tag separation  $s$ . As illustrated in Figure 9, the maximum tag spacing  $s$  is calculated so that if two adjacent tags 4a and 4b are a distance  $s + \epsilon$  apart, then there is room for another tag
- 30

4c between them, i.e. **EQ 8**.

However, if the vertex angle between two edges of length  $s + \varepsilon$  is less than  $60^\circ$ , then the inserted tags will overlap.

To prevent inserted tags from overlapping, a minimum tag separation  $t$  is introduced, where  $t \geq k$ . The minimum vertex angle  $\alpha$  then becomes a function of  $k$  and  $t$ , as shown in **EQ 9**.

Clearly, when  $t = k$ ,  $\beta$  is constrained to be  $60^\circ$ , i.e. the mesh is constrained to be equilateral. But as illustrated in Figure 56, when  $t > k$ ,  $\beta$  can be less than  $60^\circ$  without inserted tags overlapping.

10 The maximum tag separation  $s$  must be based on the new minimum tag separation  $t$ , in accordance with **EQ 10**.

When considering a particular mesh triangle, there are four distinct tag insertion scenarios. By assuming that the minimum vertex angle is no less than  $30^\circ$  (i.e. half of  $60^\circ$ ), it can be shown that whenever a mesh triangle has at least one edge less than or equal to  $s$  in length, the remaining two edges are less than  $2s$  in length. In practice the minimum vertex angle is typically at least  $45^\circ$ .

In the first scenario (Figure 57) no edges of a triangle exceed  $s$  in length, so the tagging of the triangle is already complete.

20 In the second scenario (Figure 58) one edge 548 of a triangle 550 exceeds  $s$  in length. A tag 552 is inserted at the midpoint of the edge 548 to complete the tagging of the triangle 550.

In the third scenario (Figure 59) two edges 554, 556 of a triangle 558 exceed  $s$  in length. Tags 560, 562 are inserted at the midpoint of each of the two long edges 554, 556 and this may complete the tagging of the triangle 558. Centers of the two inserted tags 560, 562 together with the two vertices 564, 566 of the short edge 568 of the original triangle 558 form a trapezoid. If either diagonal of the trapezoid exceeds  $s$  in length then a final tag 570 is inserted at the center of the trapezoid to complete the tagging of the triangle.

In the fourth scenario (Figure 60) all three edges 572 of a triangle 573 exceed  $s$

in length. A tagged vertex 574 is inserted at the midpoint of each edge 572 and the three new vertices 574 are joined by edges 576. The tagging procedure is then recursively applied to each of the four resultant triangles 577, 578, 579 and 580. Note that the new triangles respect the minimum vertex angle because they have the same shape as the original triangle 573.

The tag tiling variables are summarized in Table 4.

**Table 4. Tag tiling variables**

variable	Meaning
$\beta$	minimum vertex angle
$k$	tag diameter
$m$	minimum diameter of sensor field of view on surface
$s$	maximum center-to-center tag spacing
$t$	minimum center-to-center tag spacing

## 8.2 TAG SENSING

### 8.2.1 Pen Orientation

To allow a pen-like sensing device to be used as a comfortable writing instrument, a range of pen orientations must be supported. Since the pen nib is constrained to be in contact with the surface, the orientation of the pen can be characterized by the yaw (z rotation), pitch (x rotation) and roll (y rotation) of the pen, as illustrated in Figure 61. While the yaw of the pen must be unconstrained, it is reasonable to constrain the pitch and roll of the pen as well as the overall tilt of the pen resulting from the combination of pitch and roll.

Yaw is conventionally applied after pitch, such that, for example, in the case of a pen device it would define a twist about the physical axis rather than a direction in the surface plane. In a pen with a marking nib, however, the image sensor is mounted off the axis of the pen and the pen's image sensing ability (and hence its yaw sensing ability) is therefore constrained unless the pen is held almost vertically, as discussed below. Yaw is therefore applied before pitch, allowing the full yaw range to be specified by rotating the pen relative to the surface while keeping pitch and roll constant.



Pitch and roll are conventionally defined as y and x rotations, respectively. Here they are defined as x and y rotations, respectively, because they are defined with respect to the x-y coordinate system of the surface, where the y axis is the natural longitudinal axis and the x axis is the natural lateral axis when viewed by a user. In a right-handed 3D coordinate system, roll is conventionally defined as positive when anticlockwise, while pitch and yaw are conventionally defined as positive when clockwise. Here all rotations are defined as positive when anticlockwise.

The pen's overall tilt ( $\theta$ ) is related to its pitch ( $\phi$ ) and the roll ( $\psi$ ) in accordance with EQ 11.

The pen's tilt affects the scale at which surface features are imaged at different points in the field of view, and therefore affects the resolution of the image sensor. Since it is impractical to sense the area directly under the pen nib, the pen's tilt also affects the distance from the nib to the center of the imaged area. This distance must be known to allow a precise nib position to be derived from the position determined from the tag.

### 8.2.2 Image Sensing

The field of view can be modeled as a cone defined by a solid half-angle  $\alpha$  (giving an angular field of view of  $2\alpha$ ), and an apex height of  $D$  above the surface when the optical axis is vertical. Although the image sensor is typically rectangular, only the largest elliptical subarea of the image sensor is relevant to guaranteeing that a sufficiently large part of the surface is imaged, as quantified earlier.

The intersection of the field of view cone with the surface defines an elliptical window on the surface. This window is circular when the optical axis is vertical.

Figure 62 illustrates the geometric relationship, for a given pitch-related tilt  $\theta$  of the pen's optical axis, between the pen's nib (point A), the pen's optical axis (CE), and the field of view window (FH). The tilt is defined to be clockwise positive from the vertical. The equations which follow apply to both positive and negative tilt.

When the pen is not tilted, the window diameter (i.e.  $|BD|$ ) is given by EQ 12.

If, when the pen is not tilted, the distance from the nib to edge of the window (i.e.  $|AB|$ ) is  $T$ , then the distance  $S$  from the nib to the center of the window (i.e.

$|AC|$ ) is given by **EQ 13**.

When the pen is tilted by  $\theta$ , the distance from the viewpoint to the surface along the optical axis is reduced to  $d$  (i.e.  $|GE|$ ), given by **EQ 14**.

The width of the window (i.e.  $|FH|$ ) is then given by **EQ 15**.

5         $D$  and  $\alpha$  must be chosen so that an adequately large area is imaged throughout the supported tilt range. The required minimum diameter  $m$  of the area is given by **EQ 4**, while the width of the actual imaged area is given by **EQ 15**. This then gives **EQ 16**.

10        Once  $D$  and  $\alpha$  are determined, an image sensor resolution must be chosen so that the imaged area is adequately sampled, i.e. that the maximum feature frequency is sampled at its Nyquist rate or higher.

15        When imaged, the scale of the surface decreases with increasing distance from the viewpoint and with increasing inclination relative to the viewing ray. Both factors have maximum effect at point F for positive tilt and point H for negative tilt, i.e. at the point in the window furthest from the viewpoint. Note that references to F in the following discussion apply to H when the tilt is negative.

The distance of point F from the viewpoint (i.e.  $|EF|$ ) is given by **EQ 17**.

Scaling due to the inclination of the surface relative to the viewing ray through F ( $EF$ ) is given by **EQ 18**.

20        If the surface feature frequency is  $f$ , then the angular surface feature frequency  $\omega$  at F (i.e. with respect to the field of view) due to both factors is given by **EQ 19**.

When there is no object plane tilt (i.e.  $\theta = 0$ ), this reduces to **EQ 20**.

25        The image sensor is, by definition, required to image at least the entire angular field of view. Since the pixel density of the image sensor is uniform, it must image the entire field of view at maximum frequency. Given an angular field of view in image space of  $2\alpha'$ , an image sensor tilt (i.e. image plane tilt) with respect to the optical axis of  $\theta'$ , and a sampling rate of  $n$  (where  $n \geq 2$  according to Nyquist's theorem), the minimum image sensor resolution  $q$  is given by **EQ 21** and **EQ 22**.

The cos-squared term in the numerator in **EQ 22** results from the same

reasoning as the cos-squared term in the denominator in **EQ 19**.

When there is no image plane tilt (i.e.  $\theta' = 0$ ), and the image space and object space angular fields of view are equal (i.e.  $\alpha' = \alpha$ ), this reduces to **EQ 23** and **EQ 24**.

When there is no object plane tilt (i.e.  $\theta = 0$ ) this reduces further to **EQ 25**.

- 5        When the image plane tilt and the object plane tilt are equal (i.e.  $\theta' = \theta$ ), and the image space and object space angular fields of view are equal (i.e.  $\alpha' = \alpha$ ), **EQ 22** reduces to **EQ 26**.

Matching the image plane tilt to the object plane tilt therefore yields a smaller required image sensor size than when the image sensor tilt is fixed at zero, and  
10 eliminates perspective distortion from the captured image. Variable image sensor tilt is, however, a relatively costly option in practice, and also requires greater depth of field.

Figure 63 illustrates the geometric relationship, for a given roll-related tilt  $\theta$  of the pen's optical axis, between the pen's nib (point A), the pen's optical axis (CE), and the field of view window (FH). The tilt is again defined to be clockwise positive from  
15 the vertical. With the exception of **EQ 13**, the preceding equations apply equally to roll-induced tilt. For roll-induced tilt the distance  $S$  from the nib to the center of the window (i.e.  $|AC|$ ) is zero rather than as defined by **EQ 13**.

For pitch-induced tilt, the magnitude of the tilt range is maximised by choosing a minimum (negative) tilt and a maximum (positive) tilt which have the same image  
20 sensor requirement. Since, for pitch-induced tilt, the surface is more distant for negative tilt than for positive tilt of the same magnitude, the minimum has a smaller magnitude than the maximum. For roll-induced tilt they have the same magnitude.

As described above, the smallest features of the tag 4 are the structures which encode the data bits, and these have a minimum diameter of 8 dots. This gives a  
25 maximum feature frequency  $f$  of about 7.9 per mm at 1600 dpi.

As calculated according to **EQ 4** above, an equilateral triangular tiling of 256-dot diameter tags with no overlap between successive lines of tags requires a minimum field of view window diameter on the surface of 598 dots, or about 9.5 mm at 1600 dpi.

Most people hold a pen at about  $+30^\circ$  pitch and  $0^\circ$  roll. The inking ball of a

ball-point nib loses effective contact with the surface beyond about  $+50^\circ$  pitch (i.e.  $40^\circ$  from the horizontal). A reasonable target pitch range is therefore  $-10^\circ$  to  $+50^\circ$ , and a reasonable roll range  $-30^\circ$  to  $+30^\circ$ , bearing in mind greater limitations on combined pitch and roll as given by EQ 11.

- 5           The highly compact ( $1.5 \text{ mm}^2$ ) Matsushita CCD image sensor (Matsushita Electronic Corporation, and is described in a paper by Itakura, K T Nobusada, N Okusenya, R Nagayoshi, and M Ozaki, "A 1mm 50k-Pixel IT CCD Image Sensor for Miniature Camera System", IEEE Transactions on Electronic Devices, Volt 47, number 1, January 2000) is suitable for use in a compact device such as a pen. It has an available
- 10 resolution of  $215 \times 215$  pixels. Assuming equal image and object space angular fields of view, no image plane tilt, and a nib-to-window distance  $T$  of 4 mm, optimizing the geometry using EQ 16 and EQ 24 to achieve the desired pitch and roll ranges stated above yields a pitch range of  $-16^\circ$  to  $+48^\circ$  ( $64^\circ$ ) and a roll range of  $-28^\circ$  to  $+28^\circ$  ( $56^\circ$ ) with a viewing distance  $D$  of 30 mm and an angular field of view of  $18.8^\circ$  ( $\alpha = 9.4^\circ$ ).
- 15 The available pitch range is actually  $-21^\circ$  to  $+43^\circ$ , and this is mapped to close to the desired range by pitching the optical axis at  $-5^\circ$  relative to the physical axis. Note that the tilt range can be expanded slightly by optimizing a non-zero tilt of the image plane.

The overall pen tilt is thus confined to an elliptical cone whose major angle is  $64^\circ$  in the pitch plane and whose minor angle is  $56^\circ$  in the roll plane.

- 20           The image sensing variables are summarized in Table 5.

**Table 5. Image sensing variables**

variable	meaning
$\alpha$	Object space field of view half-angle
$\alpha'$	Image space field of view half-angle
$\gamma$	Pen yaw
$\theta$	Object plane tilt (i.e. overall pen tilt)
$\theta'$	Image plane tilt
$\phi$	Pen pitch
$\psi$	Pen roll
$\omega$	Angular frequency in field of view
$D$	Normal viewing distance

$d$	Tilted viewing distance
$f$	Surface feature frequency
$n$	Sampling rate
$q$	Image sensor resolution
$S$	Distance from nib to center of field of view on surface (when $\theta = 0$ )
$T$	Distance from nib to edge of field of view on surface (when $\theta = 0$ )

### 8.3 TAG DECODING

#### 8.3.1 Tag Image Processing and Decoding

Tag image processing is described earlier in Section 1.2.4. It culminates in knowledge of the 2D perspective transform on the tag, as well as the decoded tag data.

#### 8.3.2 Inferring the Pen Transform

Once the 2D perspective transform is obtained which accounts for the perspective distortion of the tag in the captured image, as described earlier, the corresponding discrete 3D tag transform with respect to the pen's optical axis can be inferred, as described below in Section 8.4.

Once the discrete 3D tag transform is known, the corresponding 3D pen transform can be inferred, i.e. the transform of the pen's physical axis with respect to the surface. The pen's physical axis is the axis which is embodied in the pen's shape and which is experienced by the pen's user. It passes through the nib. The relationship between the physical axis and the optical axis is illustrated in Figure 64.

It is convenient to define three coordinate spaces. In sensor space the optical axis coincides with the z axis and the viewpoint is at the origin. In pen space the physical axis coincides with the z axis and the nib is at the origin. In tag space the tag lies in the x-y plane with its center at the origin. The tag transform transforms the tag from tag space to sensor space.

Sensor space is illustrated in Figure 64. The labelling of points in Figure 64 is consistent with the labelling in Figure 62. The viewpoint is at E, the sensed point is at G,

and the nib is at A. The intersection point G between the optical axis and the surface is referred to as the sensed point. In contrast with the geometry illustrated in Figure 62 where the nib is considered as a point, here the nib is considered as a small sphere. If the nib is curved, then the tilt of the physical axis affects the offset between the sensed point  
5 and the contact point between the nib and the surface. The center point K of the spherical nib, about which the physical axis pivots, is referred to as the pivot point.

The nib makes nominal contact with the surface at point A when the optical axis is vertical. KA is defined to be parallel to the optical axis. When the pen is tilted, however, contact is at point L, as shown in Figure 65. Given the radius  $R$  of the nib, the  
10 distance of the pivot point K from the surface, e.g. at A or L, is always  $R$ .

The discrete tag transform includes the translation of the tag center from the sensed point, the 3D tag rotation, and the translation of the sensed point from the viewpoint.

Given the translation  $d$  of the sensed point from the viewpoint in the discrete  
15 tag transform, and according to **EQ 14**, the sensed point is given by **EQ 27**.

Since the physical axis only differs from the optical axis by a  $y$  translation and  $x$  rotation (i.e. pitch), the physical axis lies in the  $y$ - $z$  plane. With reference to Figure 64, where  $|AC| = S$  and  $|EC| = D$  (just as in Figure 62), it is clear that in sensor space the position of the pivot point is given by **EQ 28**.

20 The vector from the sensed point to the pivot point is therefore given by **EQ 29**.

The vector from the pivot point to the contact point is by definition a surface normal of length  $R$ . It is constructed by applying the 3D tag rotation  $M$  to a tag space surface normal, normalizing the result, and scaling by  $R$ , as shown in **EQ 30** and **EQ 31**.

25 The vector from the sensed point to the contact point is then obtained in accordance with **EQ 32**.

This is transformed into tag space by applying the inverse of the tag transform 3D rotation, and is then added to the vector from the tag center to the sensed point, to yield the vector from the tag center to the contact point in tag space, i.e. on the surface,  
30 in accordance with **EQ 33**.

This is finally added to the tag's absolute location, as implied by its tag ID, to yield the nib's desired absolute location in the tagged region: see **EQ 34**.

The final step is to infer the pen's 3D orientation from the tag's 3D orientation. The pen's discrete rotations are simply the inverses of the tag's discrete rotations, with  
5 the pen's pitch also including the effect of the pitch ( $\phi_{sensor}$ ) of the optical axis with respect to the pen's axis, as defined in **EQ 35**, **EQ 36** and **EQ 37**.

#### **8.4 INFERRING THE TAG TRANSFORM**

The image of the tag 4 captured by the image sensor contains perspective distortion due to the position and orientation of the image sensor with respect to the tag.  
10 Once the perspective targets of the tag are found in image space, an eight-degree-of-freedom perspective transform is inferred based on solving the well-understood equations relating the four tag-space and image-space point pairs. The discrete transform steps which give rise to the image of the tag are concatenated symbolically, and a set of simultaneous non-linear equations is obtained by equating corresponding terms in the  
15 concatenated transform and the perspective transform. Solving these equations yields the discrete transform steps, which include the desired tag offset from the nib, 3D tag rotation, and viewpoint offset from the surface.

##### **8.4.1 Modeling the Tag Transform**

The transform of the tag 4 from tag space to image space can be modeled as a  
20 concatenation of the following transform steps:

- x-y translate (by tag-to-viewpoint offset)
- z rotate (by tag yaw)
- x rotate (by tag pitch)
- y rotate (by tag roll)
- 25 • z translate (by tag-to-viewpoint offset)
- perspective project (with specified focal length)
- x-y scale (to viewport size)

These are concatenated symbolically to produce a single transform matrix

which effects the tag transform. Table 7 summarizes the discrete transform variables used in the following sections, together with the range of each variable.

**Table 7. Discrete transform variables and their ranges**

5

Variable	Abbrev.	Meaning	Unit transform	Range
$\gamma$	-	yaw	0	$0 \leq \gamma \leq 2\pi$
$\phi$	-	pitch	0	$-\pi/2 < \phi < \pi/2$
$\psi$	-	roll	0	$-\pi/4 < \psi < \pi/4$
$t_x$	<i>A</i>	tag-to-viewpoint x offset	0	-
$t_y$	<i>B</i>	tag-to-viewpoint y offset	0	-
$\cos\gamma$	<i>C</i>	cosine of yaw	1	$-1 \leq C \leq 1$
$\sin\gamma$	<i>D</i>	sine of yaw	0	$-1 \leq D \leq 1$
$\cos\phi$	<i>E</i>	cosine of pitch	1	$0 < E \leq 1$
$\sin\phi$	<i>F</i>	sine of pitch	0	$-1 < F < 1$
$\cos\psi$	<i>G</i>	cosine of roll	1	$0 < G \leq 1$
$\sin\psi$	<i>H</i>	sine of roll	0	$-1 < H < 1$
$t_z$	<i>I</i>	tag-to-viewpoint z offset	-	$I < 0$
$1/\lambda$	<i>J</i>	inverse focal length	-	$J > 0$
<i>S</i>	-	viewport scale	-	$S > 0$

Translate in x-y plane by  $t_x$  and  $t_y$  according to **EQ 42** (where  $A=t_x$  and  $B=t_y$ ).

Rotate about z by  $\gamma$  according to **EQ 43** (where  $C=\cos(\gamma)$  and  $D=\sin(\gamma)$ ), giving **EQ 44**.

10 Rotate about x by  $\phi$  according to **EQ 45** (where  $E=\cos(\phi)$  and  $F=\sin(\phi)$ ), giving **EQ 46**.

Rotate about y by  $\psi$  according to **EQ 47** (where  $G=\cos(\psi)$  and  $H=\sin(\psi)$ ), giving **EQ 48**, where  $K$  and  $L$  are defined by **EQ 49** and **EQ 50**.

Translate in z by  $t_z$  according to **EQ 51** (where  $I=t_z$ ), giving **EQ 52**.

15 Perspective project with focal length  $\lambda$  and projection plane at  $z=0$  according to **EQ 53** (where  $J=1/\lambda$ ), giving **EQ 54**.



Scale to viewport by  $S$  according to **EQ 55**, giving **EQ 56**.

Transform a point in the x-y plane ( $z=0$ ) according to **EQ 57**, giving **EQ 58**.

Finally, expand  $K$  and  $L$ , giving **EQ 59**.

#### **8.4.2 2D Perspective Transform**

- 5        Given an inferred eight-degree-of-freedom 2D perspective transform matrix as defined in **EQ 60**, multiply by an unknown  $i$  to obtain the general nine-degree-of-freedom form of the matrix, as shown in **EQ 61**.

Transform a 2D point according to **EQ 62**, giving **EQ 63**.

#### **8.4.3 Inferring the Tag Transform**

##### **10 8.4.3.1 Equating Coefficients**

Equating the coefficients in **EQ 59** with the coefficients in **EQ 63** results in **EQ 64** to **EQ 72**, being nine non-linear equations in 11 unknowns.

- These equations are augmented as required by the trigonometric identity relating the sine and cosine of an angle (i.e. the sine and cosine of any one of yaw, pitch  
15 and roll), as shown in **EQ 73**.

Given the sine and cosine of an angle, the corresponding angle is obtained using a two-argument arctan as shown in **EQ 74**.

##### **8.4.3.2 Solving for X-Y Offset**

- 20        **EQ 66** can be simplified using **EQ 64** and **EQ 65** to give **EQ 75** and then **EQ 76**.

**EQ 69** can be simplified using **EQ 67** and **EQ 68** to give **EQ 77** and then **EQ 78**.

- EQ 72** can be simplified using **EQ 70** and **EQ 71** to give **EQ 79** and then **EQ 80**.  
25

**EQ 76** can be re-written as **EQ 81**, and **EQ 78** can be re-written as **EQ 82**.

Equating **EQ 81** and **EQ 82** and solving for  $B$  yields **EQ 83** through **EQ 85** and

finally **EQ 86**, which defines  $B$ .

Substituting the value for  $B$  into **EQ 82** and simplifying yields **EQ 87** through **EQ 90** and finally **EQ 91**, which defines  $A$ .

5 This therefore gives the x-y offset of the tag 4 from the viewpoint, since  $A=t_x$   
and  $B=t_y$ .

#### 8.4.3.3 Solving for Pitch

From **EQ 68**, **EQ 92** can be obtained.

From **EQ 67**, **EQ 93** can be obtained.

From **EQ 64**, **EQ 92** and **EQ 93**, **EQ 94** can be obtained.

10 From **EQ 65**, **EQ 92** and **EQ 93**, **EQ 95** can be obtained.

From **EQ 70**, **EQ 92** and **EQ 93**, **EQ 96** can be obtained.

From **EQ 71**, **EQ 92** and **EQ 93**, **EQ 97** can be obtained.

From **EQ 94**, **EQ 98** can be obtained.

From **EQ 95**, **EQ 99** can be obtained.

15 From **EQ 96**, **EQ 100** can be obtained.

From **EQ 97**, **EQ 101** can be obtained.

From **EQ 98** and **EQ 99**, **EQ 102** and then **EQ 103** can be obtained.

From **EQ 100** and **EQ 101**, **EQ 104** and then **EQ 105** can be obtained.

From **EQ 103** and **EQ 105**, **EQ 106** and then **EQ 107** can be obtained.

20 **EQ 107** only has a valid basis if  $G$  and  $H$  are both non-zero. Since  $|\psi| < \pi/2$ , the cosine ( $G$ ) of the roll is always positive and hence non-zero. The sine of the roll ( $H$ ) is only non-zero if the roll is non-zero. Specific handling for zero pitch and roll is described in Section 6.7.3.10.

25 This therefore gives the magnitude of the sine of the pitch, since  $F=\sin(\phi)$ , and hence the cosine ( $E$ ) of the pitch by **EQ 73**, according to **EQ 108**.

Since  $|\phi| < \pi/2$ , the cosine ( $E$ ) of the pitch is always positive, so there is no ambiguity when taking the square root. The sign of the sine ( $F$ ), however, must be

determined by other means, as described in Section 6.7.3.9.

Given  $E$  and  $F$ , the pitch is then obtained, according to **EQ 109**.

#### 8.4.3.4 Solving for Roll

From **EQ 103**, **EQ 110** can be obtained.

5 From **EQ 73**, **EQ 111** and then **EQ 112** can be obtained.

This therefore gives the magnitude of the sine of the roll, since  $H = \sin(\psi)$ , and hence the cosine ( $G$ ) of the roll by **EQ 73**, according to **EQ 113**.

Since  $|\psi| < \pi/4$ , the cosine ( $G$ ) of the roll is always positive, so there is no ambiguity when taking the square root. The sign of the sine ( $H$ ), however, must be  
10 determined by other means, as described in Section 6.7.3.9.

Given  $G$  and  $H$ , the roll is then obtained according to **EQ 114**.

#### 8.4.3.5 Solving for Yaw

From **EQ 73**, **EQ 92** and **EQ 93**, **EQ 115** and then **EQ 116** can be obtained.

From **EQ 92** and **EQ 116**, **EQ 117** and then **EQ 118** can be obtained.

15 From **EQ 92** and **EQ 116**, **EQ 119** and then **EQ 120** can be obtained.

In **EQ 116**, and hence **EQ 118** and **EQ 120**, the sign of the square root is determined by the sign of  $i$ , which can be determined from **EQ 80**, giving **EQ 121**.

Since  $I(t_z)$  is negative,  $J(1/\lambda)$  is positive, and  $IJ < -1$  (because  $|t_z| > \lambda$ ), then **EQ 122** holds.

20 Given  $C$  and  $D$ , the yaw is then obtained according to **EQ 123**.

#### 8.4.3.6 Solving for Viewport Scale

The cosine ( $C$ ) and sine ( $D$ ) of the yaw are by definition never simultaneously zero. Since the cosine ( $E$ ) of the pitch is never zero, either **EQ 67** or **EQ 68** can therefore always be used to determine the viewport scale ( $S$ ).

25 If  $D$  is non-zero, then from **EQ 67**, **EQ 124** can be obtained.

Otherwise, if  $C$  is non-zero, then from **EQ 68**, **EQ 125** can be obtained.

#### 8.4.3.7 Solving for Focal Length

Similarly, since the cosine ( $G$ ) of the roll is never zero, either EQ 70 or EQ 71 can be used to determine the inverse focal length ( $J$ ), so long as either the pitch or roll is non-zero. However, the signs of the sines ( $F$  and  $H$ ) of the pitch and roll may not be known. However, the sign of the product ( $FH$ ) of the sines of the pitch and roll is given by EQ 103, as shown in EQ 126.

The sign can be assigned arbitrarily to  $F$ , since the sign of  $J$  is known a priori. If  $g_i$  is non-zero, then from EQ 70, EQ 127 can be obtained.

If  $h_i$  is non-zero, then from EQ 71, EQ 128 can be obtained.

10 In practice, the choice between using EQ 127 and EQ 128 is based on which of  $g_i$  and  $h_i$  has the larger magnitude. The inverse focal length is unknown if  $g_i$  and  $h_i$  are both zero, i.e. if the pitch and roll are both zero.

#### 8.4.3.8 Solving for Z Offset

Once the inverse focal length ( $J$ ) is known, the z offset ( $I$ ) is obtained from EQ 15 80, according to EQ 129.

Again, the z offset ( $I$ ) is unknown if the inverse focal length ( $J$ ) is unknown, i.e. if the pitch and roll are both zero.

#### 8.4.3.9 Determining Direction of Pitch and Roll

20 The sign of the product ( $FH$ ) of the sines of the pitch and roll is given by EQ 126. Since  $-\pi/4 < \psi < \pi/4$ , a roll adjustment of  $+\pi/4$  can be introduced to ensure the roll is always positive, without invalidating any other assumptions. Once the roll adjustment is introduced, EQ 126 gives the sign of the sine ( $F$ ) of the pitch alone.

25 The roll adjustment is introduced as follows. The viewport scale ( $S$ ), inverse focal length ( $J$ ), and z offset ( $I$ ) are all computed as described. A 3D transform matrix is created from the 2D perspective transform matrix. The inverses of the viewport scale, focal length projection and z translation are applied to the 3D matrix in reverse order. The roll adjustment is then applied by pre-multiplying the matrix by a  $\pi/4$  y rotation matrix. The roll, pitch and yaw are computed as described. Since the roll is positive, the pitch direction is now known. The  $\pi/4$  roll adjustment is finally subtracted from the roll

to give the actual roll.

When the roll and pitch are both zero, the focal length and z offset are both unknown as described above. However, in this case there is no need to adjust the roll since the pitch and roll are already known.

#### 5    **8.4.3.10 Handling Zero Pitch and Roll**

When either the pitch or roll is zero, the general solution based on **EQ 107** becomes invalid. The table of Figure 85 shows the 12 degenerate forms of **EQ 64** through **EQ 71** which result when the yaw is variously zero (or  $\pi$ ),  $\pi/2$  (or  $3\pi/2$ ), and non-zero, and the pitch and roll are variously zero and non-zero. The table of Figures 86 and 87 sets out the required logic for detecting and handling cases where the pitch and/or roll are zero, with each case motivated by zeros appearing in the table of Figure 85. The cases in the table of Figure 85 are labelled with the case numbers from the table of Figures 86 and 87.

#### **CONCLUSION**

The present invention has been described with reference to a preferred embodiment and number of specific alternative embodiments. However, it will be appreciated by those skilled in the relevant fields that a number of other embodiments, differing from those specifically described, will also fall within the spirit and scope of the present invention. Accordingly, it will be understood that the invention is not intended to be limited to the specific embodiments described in the present specification, including documents incorporated by cross-reference as appropriate. The scope of the invention is only limited by the attached claims.

## CLAIMS

1. A region defined in relation to a surface, coded data being disposed within the  
5 region, wherein the coded data is indicative of:
  - a region identity associated with the region; and
  - a plurality of points within the region.
2. A region according to claim 1, wherein the coded data includes at least one tag,  
10 each tag being indicative of the region identity and the position of the tag within the region.
3. A region according to claim 2, wherein each of the tags includes:
  - first identity data defining a relative position of that tag; and
  - 15 second identity data identifying the surface.
4. A region according to claim 3, including further tags that do not include both first identity data and second identity data.
- 20 5. A region according to claim 3, wherein the relative position is defined in relation to the surface.
6. A region according to claim 3, wherein the relative position is defined in relation to a plurality of the other tags.
- 25 7. A region according to claim 3, wherein the first identity data identifies stored information defining the relative position, the stored information not being stored on the

surface.

8. A region according to claim 3, wherein the first identity data and the second identity data together identify stored information defining the relative position.

5

9. A region according to claim 3, wherein the surface is defined by a substrate.

10. A region according to claim 9, wherein the substrate is laminar.

10 11. A region according to claim 3, wherein the tags are disposed at predetermined positions on the surface.

12. A region according to claim 11, wherein the tags are disposed on the surface within a tessellated pattern comprising a plurality of tiles, each of the tiles containing a  
15 plurality of the tags.

13. A region according to claim 12, wherein the tiles interlock with each other to substantially cover the surface.

20 14. A region according to claim 13, wherein the tiles are all of a similar shape.

15. A region according to claim 14, wherein the tiles are triangular, square, rectangular or hexagonal.

25 16. A region according to claim 12, wherein the tags are disposed stochastically within each of the tiles.

17. A region according to claim 16, wherein the first identity data of each of the tags includes index data indicating the tile within which the tag is disposed and position data indicating the tag's position within that tile.

5 18. A region according to claim 3, wherein each of the tags includes at least one common feature in addition to the second identity data.

10 19. A region according to claim 18, wherein the at least one common feature is configured to assist finding and/or recognition of the tags by associated tag reading apparatus.

20. A region according to claim 18, wherein the at least one common feature is represented in a data format incorporating redundancy of information.

15 21. A region according to claim 20, wherein the at least one common feature is rotationally symmetric so as to be rotationally invariant.

22. A region according to claim 20, wherein the at least one common feature is ring-shaped.

20

23. A region according to claim 3, wherein each of the tags includes at least one orientation feature for enabling a rotational orientation of the tag being read to be ascertained.

25 24. A region according to claim 23, wherein the at least one orientation feature is represented in a format incorporating redundancy of information.

25. A region according to claim 24, wherein the at least one orientation feature is



rotationally asymmetric.

26. A region according to claim 24, wherein the at least one orientation feature is skewed along its major axis.

5

27. A region according to claim 3, wherein each of the tags includes at least one perspective feature for enabling a perspective distortion of the tag being read to be ascertained.

10 28. A region according to claim 27, wherein the at least one perspective feature includes at least four sub-features which are not coincident.

15 29. A region according to claim 3, wherein each tag includes a plurality of tag elements, the first and second identity data each being defined by a plurality of the elements.

30. A region according to claim 29, wherein the tag elements are disposed in one or more arcuate bands around a central region of each tag.

20 31. A region according to claim 30, wherein there are a plurality of the arcuate bands disposed concentrically with respect to each other.

32. A region according to claim 31, wherein each element takes the form of a dot having a plurality of possible values.

25

33. A region according to claim 32, wherein the number of possible values is two.

34. A region according to claim 32, wherein when representing one of the possible values, the tag elements absorb, reflect or fluoresce electromagnetic radiation of a predetermined wavelength or range of wavelengths to a predetermined greater or lesser extent than the surface.

5

35. A region according to claim 32, wherein the possible values of the tag elements are defined by different relative absorption, reflection or fluorescence of electromagnetic radiation of a predetermined wavelength or range of wavelengths.

10 36. A region according to claim 32, wherein the tags are not substantially visible to an average unaided human eye under daylight or ambient lighting conditions.

37. A region according to claim 32, wherein the tags are slightly visible to an average unaided human eye under daylight or ambient lighting conditions.

15

38. A region according to claim 32, wherein the tags are visible to an average unaided human eye under daylight or ambient lighting conditions.

39. A region according to claim 3, wherein the first identity data is represented in a  
20 format incorporating redundancy of information.

40. A region according to claim 3, wherein the second identity data is represented in a format incorporating redundancy of information.

25 41. A region according to claim 2, wherein the tags are printed onto the surface by means of a printer.

42. A region according to claim 41, wherein the printer is an ink printer.

43. A region according to claim 42, wherein the tags are printed using ink that is absorbent or reflective in the ultraviolet spectrum or the infrared spectrum.

5 44. A region according to claim 41, wherein the printer also prints additional information onto the surface.

45. A region according to claim 44, wherein the additional information is printed onto the surface using colored or monochrome inks.

10

46. A region according to claim 45, wherein the additional information is printed onto the surface using one of the following combinations of colored inks:

CMY;

CMYK;

15

CMYRGB; and

spot colour.

47. A region according to claim 2, wherein at least a plurality of the tags are disposed stochastically upon the surface.

20

48. A region according to claim 47, wherein the first identity data of each of the tags includes position data indicating the tag's position in relation to either the surface or a plurality of the other tags.

25 49. A region according to claim 48, wherein the tags are disposed in a regular array on the surface.

50. A region according to claim 49, wherein the array is triangular.
51. A region according to claim 50, wherein the tags are tiled over the surface
- 5 52. A region according to claim 49, wherein the array is rectangular.
53. A region according to claim 52, wherein the tags are tiled over the surface.
54. A region according to claim 2, further including additional non-tag information  
10 disposed on the surface
55. A region according to claim 1, wherein the region is identified with sufficient precision to distinguish the region from  $1.5 \times 10^{14}$  other regions.
- 15 56. A region according to claim 1, wherein any 10 millimetre diameter subregion of the region includes sufficient coded data to identify the region.
57. A region according to claim 56, wherein any 10 millimetre diameter subregion of the region includes sufficient information to identify at least one point of the region.
- 20 58. A surface, including a region according to any one of the preceding claims.
59. A method of producing a surface having a region, the method including the steps of:
- 25 (a) defining coded data, the coded data being indicative of:  
a region identity associated with the region; and

a plurality of points within the region;

(b) disposing the coded data within a region on the surface

60. A method according to claim 59, wherein the coded data includes at least one tag, each tag being indicative of the region identity and the position of the tag within the region.

61. A method according to claim 60, wherein each of the tags includes:  
first identity data defining a relative position of that tag; and  
second identity data identifying the surface.

62. A method according to claim 61, wherein the respective first identity data associated with each tag defines the position of that tag with respect to the surface.

63. A method according to claim 61, wherein the respective first identity data associated with each tag defines a position of that tag with respect to one or more other tags.

64. A method according to claim 59, including the step of providing a substrate upon which the surface is defined, the step being performed at any suitable time in relation to the other steps of the method.

65. A method according to claim 60, wherein step (b) includes the sub-step (b)(i) of disposing the tags at predetermined positions on the surface.

66. A method according to claim 65, wherein sub-step (b)(i) includes the step of disposing the tags in a regular array on the surface.

67. A method according to claim 65, wherein sub-step (b)(i) includes the step of disposing the tags in a rectangular array on the surface.

5 68. A method according to claim 66, wherein the step of disposing the tags on the surface includes the sub-step of tiling the tags over the surface.

69. A method according to claim 60, further including the step of adding a common feature to the tags in addition to the second identity data.

10

70. A method according to claim 69, wherein the common feature is configured to assist location and/or recognition of the tags by associated tag reading apparatus.

15 71. A method according to claim 69, wherein the common features are represented in a format incorporating redundancy of information.

72. A method according to claim 60, further including the step of providing each of the tags with one or more orientation features for enabling an orientation of the tag being read to be ascertained.

20

73. A method according to claim 72, wherein the orientation features are represented in a format incorporating redundancy of information.

25 74. A method according to claim 43, wherein each tag includes a plurality of tag elements, the first and second identity data being defined by a plurality of the elements.

75. A method according to claim 74, wherein the tag elements are disposed in one

or more arcuate bands around a central region of each tag.

76. A method according to claim 75, wherein there are a plurality of the arcuate bands disposed concentrically with respect to each other.

5

77. A method according to claim 76, wherein each element takes the form of a dot having a plurality of possible values.

78. A method according to claim 77, wherein the number of possible values is two.

10

79. A method according to claim 77, wherein when representing one of the possible values, the tag elements absorb, reflect or fluoresce electromagnetic radiation of a predetermined wavelength or range of wavelengths to a predetermined greater or lesser extent than the surface.

15

80. A method according to claim 77, wherein the possible values of the tag elements are defined by different relative absorption, reflection or fluorescence of electromagnetic radiation of a predetermined wavelength or range of wavelengths.

20 81. A method according to claim 77, wherein the tags are not substantially visible to an average unaided human eye under daylight or ambient lighting conditions.

82. A method according to claim 77, wherein the tags are slightly visible to an average unaided human eye under daylight or ambient lighting conditions.

25

83. A method according to claim 77, wherein the tags are visible to an average unaided human eye under daylight or ambient lighting conditions.

84. A method according to claim 61, wherein the first identity data is represented in a format incorporating redundancy of information.

5 85. A method according to claim 61, wherein the second identity data is represented in a format incorporating redundancy of information.

86. A method according to claim 60, wherein the tags are printed onto the surface by means of a printer.

10

87. A method according to claim 86, wherein the printer is an ink printer.

88. A method according to claim 87, wherein the tags are printed using ink that is absorbent or reflective in the ultraviolet spectrum or the infrared spectrum.

15

89. A method according to claim 86, wherein the printer also prints additional information onto the surface.

90. A method according to claim 89, wherein the additional information is printed  
20 onto the surface using colored or monochrome inks.

91. A method according to claim 90, wherein the additional information is printed onto the surface using one of the following combinations of colored inks:

CMY;

25

CMYK;

CMYRGB; and

spot colour.



92. A method according to claim 60, wherein at least a plurality of the tags are disposed stochastically upon the surface.

5 93. A method according to claim 92, wherein the first identity data of each of the tags includes position data indicating the tag's position in relation to either the surface or a plurality of the other tags.

10 94. A method according to claim 93, wherein the tags are disposed in a regular array on the surface.

95. A method according to claim 94, wherein the array is triangular.

15 96. A method according to claim 95, wherein the tags are tiled over the surface

97. A method according to claim 94, wherein the array is rectangular.

98. A method according to claim 97, wherein the tags are tiled over the surface.

20 99. A method according to claim 60, further including additional non-tag information disposed on the surface

100. A method according to claim 59, wherein the region is identified with sufficient precision to distinguish the region from  $1.5 \times 10^{14}$  other regions.

25

101. A method according to claim 59, wherein any 10 millimetre diameter subregion of the region includes sufficient coded data to identify the region.

102. A method according to claim 101, wherein any 10 millimetre diameter subregion of the region includes sufficient information to identify at least one point of the region.

5

103. A method according to claim 63, wherein step (b) includes the sub-step of disposing the readable tags on the surface such that the relative spacing of their centres is less than about 12mm.

10 104. A method according to claim 103, wherein the relative spacing is less than about 3mm.

105. A method according to claim 103, wherein the relative spacing is less than about 1mm.

15

106. A region according to any one of claims 1 to 3, 7, 8, 18, 24 or 29 to 35, wherein the coded data is machine readable, and the information represented by the coded data is substantially inscrutable to an unaided human.

20 107. A method according to any one of claims 59 to 61, 69, 72 or 74 to 80, wherein the coded data is machine readable, and the information represented by the coded data is substantially inscrutable to an unaided human.

## ABSTRACT

A region defined in relation to a surface, and a method for defining such a region; coded data being disposed within the region, the coded data being indicative of an identity of  
5 the region and of a plurality of points within the region; in one embodiment, the coded data comprising a plurality of tags, each tag being indicative of the region identity and of its own position within the region.





FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 12a




FIG. 13






FIG. 14




FIG. 15




FIG. 16




FIG. 17





FIG. 18






FIG. 20




FIG. 21






FIG. 22




FIG. 23






FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34






FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 38a




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44






FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56






FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66

EQ NUMBER	EQUATION
1	$m = k\left(\frac{2}{\sqrt{3}} + 1\right)$
2	$m = \frac{2s}{\sqrt{3}} + k$
3	$u = k\left(\frac{2}{\sqrt{3}} - 1\right)$
4	$m = \frac{7k}{3}$
5	$\theta = 2\arcsin\left(\frac{2}{\sqrt{10 + 2\sqrt{5}}}\right) \cong 63.4^\circ \cong 1.11 \text{ radians}$
6	$n = 10v^2 + 2 = 10\left[\frac{\theta r}{K}\right]^2 + 2$
7	$r \leq \frac{K}{\theta} \left[ \sqrt{\frac{n-2}{10}} \right]$
8	$s \geq 2k$
9	$\beta = 2\arcsin \frac{k}{2t}$
10	$s \geq 2t$

FIG. 67



EQ NUMBER	EQUATION
11	$\sin \theta = \cos \phi \cos \psi$
12	$2D \tan \alpha$
13	$S = T + D \tan \alpha$
14	$d = D - S \tan \theta$
15	$d \cos \theta (\tan(\theta + \alpha) - \tan(\theta - \alpha))$
16	$d \cos \theta (\tan(\theta + \alpha) - \tan(\theta - \alpha)) \geq m$
17	$\frac{d \cos \theta}{\cos( \theta  + \alpha)}$
18	$\cos( \theta  + \alpha)$
19	$\omega = \frac{f d \cos \theta}{\cos^2( \theta  + \alpha)}$
20	$\omega_0 = \frac{f D}{\cos^2 \alpha}$

FIG. 68

EQ NUMBER	EQUATION
21	$q = 2\alpha'n\omega\cos^2( \theta'  + \alpha')$
22	$q = \frac{2\alpha'nfd\cos\theta\cos^2( \theta'  + \alpha')}{\cos^2( \theta  + \alpha)}$
23	$q = \frac{2\alpha nfd\cos\theta\cos^2\alpha}{\cos^2( \theta  + \alpha)}$
24	$q = \frac{2\alpha nfd}{\cos\theta(1 - \tan \theta \tan\alpha)^2}$
25	$q_0 = 2\alpha nfd$
26	$q = 2\alpha nfd\cos\theta$

FIG. 69

EQ NUMBER	EQUATION
27	$P_{sensed} = \begin{pmatrix} 0 \\ 0 \\ -d \end{pmatrix}$
28	$P_{pivot} = \begin{pmatrix} 0 \\ S \\ R - D \end{pmatrix}$
29	$\vec{V}_{pivot-sensed} = P_{pivot} - P_{sensed} = \begin{bmatrix} 0 \\ S \\ R - D + d \end{bmatrix}$
30	$\vec{N} = M \begin{bmatrix} 0 \\ 0 \\ 1 \end{bmatrix}$
31	$\vec{V}_{contact-pivot} = R \frac{\vec{N}}{ \vec{N} }$
32	$\vec{V}_{contact-sensed} = \vec{V}_{contact-pivot} - \vec{V}_{pivot-sensed}$
33	$\vec{V}_{contact-tag} = \vec{V}_{sensed-tag} + M^{-1} \vec{V}_{contact-sensed}$
34	$P_{contact} = P_{tag} + \vec{V}_{contact-tag}$

FIG. 70

EQ NUMBER	EQUATION
35	$\gamma_{pen} = -\gamma_{tag}$
36	$\phi_{pen} = -\phi_{tag} - \phi_{sensor}$
37	$\psi_{pen} = -\psi_{tag}$
38	$\lambda_S < \frac{\lambda_T}{2}$
39	$P_{i+1} - P_i = \lambda_S$
40	$ \lambda_T - (P_{i+1} - P_i)  = \lambda_S$
41	$\lambda_S = \frac{\lambda_T}{2}$

FIG. 71

EQ NUM	EQUATION
42	$M_1 = T_{xy} = \begin{bmatrix} 1 & 0 & 0 & A \\ 0 & 1 & 0 & B \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$
43	$R_z = \begin{bmatrix} C & -D & 0 & 0 \\ D & C & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$
44	$M_2 = R_z M_1 = \begin{bmatrix} C & -D & 0 & AC - BD \\ D & C & 0 & AD + BC \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$

FIG. 72

EQ NUM	EQUATION
45	$R_x = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & E & -F & 0 \\ 0 & F & E & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$
46	$M_3 = R_x M_2 = \begin{bmatrix} C & AC - BD & ADE + BCE \\ DE & -F & ADF + BCF \\ DF & E & 1 \\ 0 & 0 & 0 \end{bmatrix}$
47	$R_y = \begin{bmatrix} G & 0 & H & 0 \\ 0 & 1 & 0 & 0 \\ -H & 0 & G & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$

FIG. 73

EQ NUM	EQUATION
48	$M_4 = R_y M_3 = \begin{bmatrix} CG + DFH & CFH - DG & EH & GK + HL \\ DE & CE & -F & ADE + BCE \\ DFG - CH & DH + CFG & EG & GL - HK \\ 0 & 0 & 0 & 1 \end{bmatrix}$
49	$K = AC - BD$
50	$L = ADF + BCF$
51	$T_z = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & I \\ 0 & 0 & 0 & 1 \end{bmatrix}$

FIG. 74

EQ NUM	EQUATION
52	$M_5 = T_z M_4 = \begin{bmatrix} CG + DFH & CFH - DG & EH & GK + HL \\ DE & CE & -F & ADE + BCE \\ DFG - CH & DH + CFG & EG & GL - HK + I \\ 0 & 0 & 0 & 1 \end{bmatrix}$
53	$M_p = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & J & 1 \end{bmatrix}$
54	$M_6 = M_p M_5 = \begin{bmatrix} CG + DFH & CFH - DG & EH & GK + HL \\ DE & CE & -F & ADE + BCE \\ 0 & 0 & 0 & 0 \\ J(DFG - CH) & J(DH + CFG) & EGJ & J(GL - HK + I) + 1 \end{bmatrix}$

FIG. 75



Copyright 2000 by The McGraw-Hill Companies, Inc.

EQ NUM	EQUATION
55	$M_s = \begin{bmatrix} S & 0 & 0 & 0 \\ 0 & S & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$
56	$M_7 = M_s M_6 = \begin{bmatrix} S(CG + DFH) & S(CFH - DG) & SEH & S(GK + HL) \\ SDE & SCE & -SF & S(ADE + BCE) \\ 0 & 0 & 0 & 0 \\ J(DFG - CH) & J(DH + CFG) & EGJ & J(GL - HK + I) + 1 \end{bmatrix}$
57	$P_1 = M_7 \begin{bmatrix} x \\ y \\ 0 \\ 1 \end{bmatrix}$

FIG. 76

EQ NUM	EQUATION
58	$P_1 = \frac{S(CG + DFH)x + S(CFH - DG)y + S(GK + HL)}{SDEx + SCEy + S(ADE + BCE)} \left[ \frac{0}{J(DFG - CH)x + J(DH + CFG)y + J(GL - HK + I) + 1} \right]$
59	$P_1 = \frac{S(CG + DFH)x + S(CFH - DG)y + S(ACG - BDG + ADFH + BCFH)}{SDEx + SCEy + S(ADE + BCE)} \left[ \frac{0}{J(DFG - CH)x + J(DH + CFG)y + J(BDH - ACH + ADFG + BCFG + I) + 1} \right]$

FIG. 77

EQ NUMBER	EQUATION
60	$M_{p2Dinf} = \begin{bmatrix} a & b & c \\ d & e & f \\ g & h & 1 \end{bmatrix}$
61	$M_{p2D} = \begin{bmatrix} ai & bi & ci \\ di & ei & fi \\ gi & hi & i \end{bmatrix}$
62	$P_2 = M_{per2D} \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$
63	$P_2 = \begin{bmatrix} aix + biy + ci \\ dix + eiy + fi \\ gix + hiy + i \end{bmatrix}$

FIG. 78

EQ NUMBER	EQUATION
64	$\frac{ai}{S} = CG + DFH$
65	$\frac{bi}{S} = CFH - DG$
66	$\frac{ci}{S} = ACG - BDG + ADFH + BCFH$
67	$\frac{di}{S} = DE$
68	$\frac{ei}{S} = CE$
69	$\frac{fi}{S} = ADE + BCE$
70	$gi = J(DFG - CH)$
71	$hi = J(DH + CFG)$
72	$i = J(BDH - ACH + ADFG + BCFG + I) + 1$
73	$\sin^2 \theta + \cos^2 \theta = 1$
74	$\theta = \arctan(\sin \theta, \cos \theta)$

FIG. 79

EQ NUMBER	EQUATION
75	$\frac{ci}{S} = A(CG + DFH) + B(CFH - DG)$
76	$c = Aa + Bb$
77	$\frac{fi}{S} = A(DE) + B(CE)$
78	$f = Ad + Be$
79	$i = AJ(DFG - CH) + BJ(DH + CFG) + IJ + 1$
80	$i = Agi + Bhi + IJ + 1$
81	$A = \frac{c-Bb}{a}$
82	$A = \frac{f-Be}{d}$
83	$\frac{c-Bb}{a} = \frac{f-Be}{d}$
84	$cd - Bbd = af - Bae$
85	$B(ae - bd) = af - cd$
86	$B = \frac{af - cd}{ae - bd}$

FIG. 80

EQ NUMBER	EQUATION
87	$A = \frac{f - \left( \frac{af - cd}{ae - bd} \right) e}{d}$
88	$A = \frac{f(ae - bd) - e(af - cd)}{d(ae - bd)}$
89	$A = \frac{aef - bdf - aef + cde}{d(ae - bd)}$
90	$A = \frac{-bdf + cde}{d(ae - bd)}$
91	$A = \frac{-bf + ce}{ae - bd}$
92	$C = \frac{ei}{ES}$
93	$D = \frac{di}{ES}$
94	$a = \frac{e}{E}G + \frac{d}{E}FH$
95	$b = \frac{-d}{E}G + \frac{e}{E}FH$
96	$g = \frac{-e}{ES}H + \frac{d}{ES}FG$
97	$h = \frac{d}{ES}H + \frac{e}{ES}FG$
98	$E = \frac{eG + dFH}{a}$
99	$E = \frac{-dG + eFH}{b}$

FIG. 81

EQ NUMBER	EQUATION
100	$ES = \frac{-eH + dFG}{g}$
101	$ES = \frac{dH + eFG}{h}$
102	$\frac{eG + dFH}{a} = \frac{-dG + eFH}{b}$
103	$\frac{FH}{G} = \frac{ad + be}{ae - bd}$
104	$\frac{-eH + dFG}{g} = \frac{dH + eFG}{h}$
105	$\frac{FG}{H} = \frac{dg + eh}{dh - eg}$
106	$\frac{FH}{G} \times \frac{FG}{H} = \frac{(ad + be)(dg + eh)}{(ae - bd)(dh - eg)} = F^2$
107	$F = \pm \sqrt{\frac{(ad + be)(dg + eh)}{(ae - bd)(dh - eg)}}$
108	$E = \pm \sqrt{1 - F^2}$
109	$\phi = \arctan(E, F)$
110	$\frac{1}{F} \times \frac{FH}{G} = \frac{H}{G} = \left( \pm \sqrt{\frac{(ae - bd)(dh - eg)}{(ad + be)(dg + eh)}} \right) \times \frac{(ad + be)}{(ae - bd)}$ $= \pm \sqrt{\frac{(ad + be)(dh - eg)}{(ae - bd)(dg + eh)}}$
111	$\frac{H}{G} = \frac{H}{\pm \sqrt{1 - H^2}} = \frac{1}{\pm \sqrt{\frac{1}{H^2} - 1}}$

FIG. 82

EQ NUMBER	EQUATION
112	$H = \frac{1}{\pm \sqrt{\frac{1}{\left(\frac{H}{G}\right)^2} + 1}}$
113	$G = \pm \sqrt{1 - H^2}$
114	$\psi = \arctan(G, H)$
115	$\left(\frac{ei}{ES}\right)^2 + \left(\frac{di}{ES}\right)^2 = 1$
116	$\frac{S}{i} = \frac{\pm \sqrt{d^2 + e^2}}{E}$
117	$C = \frac{e}{E} \times \frac{E}{\pm \sqrt{d^2 + e^2}}$
118	$C = \frac{e}{\pm \sqrt{d^2 + e^2}}$
119	$D = \frac{d}{E} \times \frac{E}{\pm \sqrt{d^2 + e^2}}$
120	$D = \frac{d}{\pm \sqrt{d^2 + e^2}}$

FIG. 83



EQ NUMBER	EQUATION
121	$i(1 - Ag - Bh) = IJ + 1$
122	$\text{sign}(i) = -\text{sign}(1 - Ag - Bh)$
123	$\gamma = \arctan(D, C)$
124	$S = \frac{di}{DE}$
125	$S = \frac{ei}{CE}$
126	$\text{sign}(FH) = \text{sign}\left(\frac{ad + be}{ae - bd}\right)$
127	$J = \left  \frac{gi}{-CH + \text{sign}(FH)DFG} \right $
128	$J = \left  \frac{hi}{DH + \text{sign}(FH)CFG} \right $
129	$I = \frac{(i - Agi - Bhi - 1)}{J}$

FIG. 84

case	C,D	E,F	G,H	ai	bi	ci	di	ei	fi	gi	hi
1a	$\pm 1,0$	1,0	1,0	$\pm S$	0	$\pm AS$	0	$\pm S$	$\pm BS$	0	0
1b	0, $\pm 1$	1,0	1,0	0	$\pm(-S)$	$\pm(-BS)$	$\pm S$	0	$\pm AS$	0	0
1c	C,D	1,0	1,0	CS	-DS	Aai+Bbi	DS	CS	BS	0	0
2a	$\pm 1,0$	E,F	1,0	$\pm S$	0	$\pm AS$	0	$\pm ES$	Bei	0	$\pm FJ$
2b	0, $\pm 1$	E,F	1,0	0	$\pm(-S)$	$\pm(-BS)$	$\pm ES$	0	Adi	$\pm FJ$	0
2c	C,D	E,F	1,0	CS	-DS	Aai+Bbi	DES	CES	Adi+Bei	DFJ	CFJ
3a	$\pm 1,0$	1,0	G,H	$\pm GS$	0	Aai	0	$\pm S$	$\pm BS$	$\pm(-HJ)$	0
3b	0, $\pm 1$	1,0	G,H	0	$\pm(-GS)$	Bbi	$\pm S$	0	$\pm AS$	0	$\pm HJ$
3c	C,D	1,0	G,H	CGS	-DGS	Aai+Bbi	DS	CS	Adi+Bei	-CHJ	DHJ
4a	$\pm 1,0$	E,F	G,H	$\pm GS$	$\pm FHS$	Aai+Bbi	0	$\pm ES$	Bei	$\pm(-HJ)$	$\pm FGJ$
4b	0, $\pm 1$	E,F	G,H	$\pm FHS$	$\pm(-GS)$	Aai+Bbi	$\pm ES$	0	Adi	$\pm FGJ$	$\pm HJ$
4c	C,D	E,F	G,H	CGS+ DFHS	-DGS+ CFHS	Aai+Bbi	DES	CES	Adi+Bei	-CHJ+ DFGJ	DHJ+ CFGJ

FIG. 85

description	case	condition	handling
zero pitch & zero roll	1	$g = h = 0$	$E \leftarrow 1$ $F \leftarrow 0$ $G \leftarrow 1$ $H \leftarrow 0$
zero roll	2a	$b = d = g = 0$	$E \leftarrow \frac{e}{a}$ $\frac{FJ}{S} = \frac{h}{a}$
	2b	$a = e = h = 0$	$E \leftarrow \frac{-d}{b}$ $\frac{FJ}{S} = \frac{-g}{b}$
	2c	$\frac{a}{b} = \frac{-h}{g}$	handle via 2a or 2b
	2		$G \leftarrow 1$ $H \leftarrow 0$ $F \leftarrow \text{sign}\left(\frac{FJ}{S}\right) \sqrt{1 - E^2}$

FIG. 86

description	case	condition	handling
zero pitch	3a	$b = d = h = 0$	$G \leftarrow \frac{a}{e}$ $\frac{HJ}{S} = \frac{-g}{e}$
	3b	$a = e = g = 0$	$G \leftarrow \frac{-b}{d}$ $\frac{HJ}{S} = \frac{h}{d}$
	3c	$\frac{a}{b} = \frac{g}{h}$	handle via 3a or 3b
	3		$E \leftarrow 1$ $F \leftarrow 0$ $H = \text{sign}\left(\frac{HJ}{S}\right) \sqrt{1 - G^2}$
non-zero pitch & non-zero roll	4	$(g \neq 0) \wedge (h \neq 0)$	handle via general solution

FIG. 87

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)  
Approved for use through 9/30/00. OMB 0651-0032  
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

<b>DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)</b>  <input checked="" type="checkbox"/> Declaration Submitted with Initial Filing      OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)	<b>Attorney Docket Number</b>	NPT001US
	<b>First Named Inventor</b>	Paul Lapstun
	<b>COMPLETE IF KNOWN</b>	
	<b>Application Number</b>	/
	<b>Filing Date</b>	
	<b>Group Art Unit</b>	
	<b>Examiner Name</b>	

**As a below named inventor, I hereby declare that:**

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**IDENTITY-CODED INTERFACE SURFACE WITH REFERENCE POINTS**

the specification of which (Title of the Invention)  
☒ is attached hereto  
OR  
☐ was filed on (MM/DD/YYYY) [ ] as United States Application Number or PCT International Application Number [ ] and was amended on (MM/DD/YYYY) [ ] (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
PQ0559	Australia	05/25/1999	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
PQ1313	Australia	06/30/1999	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
PQ3457	Australia	10/15/1999	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
PQ4392	Australia	12/01/1999	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box →



PTO/SB/01 (12-97)  
Approved for use through 9/30/00. OMB 0651-0032  
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

## DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number  → ☐ Registered practitioner(s) name/registration number listed below

Place Customer  
Number Bar Code  
Label here

Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☒ Customer Number or Bar Code Label  OR ☐ Correspondence address below

Name	Kia Silverbrook				
Address	Silverbrook Research Pty Ltd				
Address	393 Darling Street				
City	Balmain	State	NSW	ZIP	2041
Country	Australia	Telephone	61-2-9818-6633	Fax	61-2-9818-6711

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:  ☐ A petition has been filed for this unsigned inventor



Given Name (first and middle (if any))		Family Name or Surname	
Paul		Lapstun	
Inventor's Signature			Date
Residence: City	Rodd Point	State	NSW
Country	Australia	Citizenship	Norwegian
Post Office Address	13 Duke Avenue		
Post Office Address			
City	Rodd Point	State	NSW
ZIP	2046	Country	Australia

☒ Additional inventors are being named on the 1 supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → ☐PTO/SB/02A (3-97)  
Approved for use through 9/30/98. OMB 0651-0032  
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

**DECLARATION****ADDITIONAL INVENTOR(S)**  
**Supplemental Sheet**  
Page 1 of 1

<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Kia				Silverbrook			
Inventor's Signature						Date	May 16, 2000
Residence: City	Balmain	State	NSW	Country	Australia	Citizenship	Australian
Post Office Address	393 Darling Street						
Post Office Address							
City	Balmain	State	NSW	ZIP	2041	Country	Australia
<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Simon Robert				Walmsley			
Inventor's Signature						Date	May 16, 2000
Residence: City	Epping	State	NSW	Country	Australia	Citizenship	Australian
Post Office Address	Unit 3, 9 Pembroke Street						
Post Office Address							
City	Epping	State	NSW	ZIP	Australia	Country	Australia
<b>Name of Additional Joint Inventor, if any:</b>				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle [if any])				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.